

ISO 17636-2:2013-01 (E)

Non-destructive testing of welds - Radiographic testing - Part 2: X- and gamma-ray techniques with digital detectors

| Contents | | Page |
|------------------------------|--|-------------|
| Foreword | | iv |
| Introduction | | v |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 2 |
| 4 | Symbols and terms | 5 |
| 5 | Classification of radiographic techniques | 6 |
| 6 | General | 7 |
| 6.1 | Protection against ionizing radiation | 7 |
| 6.2 | Surface preparation and stage of manufacture | 7 |
| 6.3 | Location of the weld in the radiograph | 8 |
| 6.4 | Identification of radiographs | 8 |
| 6.5 | Marking | 8 |
| 6.6 | Overlap of digital images | 8 |
| 6.7 | Types and positions of image quality indicators (IQI) | 8 |
| 6.8 | Minimum image quality values | 9 |
| 6.9 | Personnel qualification | 10 |
| 7 | Recommended techniques for making digital radiographs | 10 |
| 7.1 | Test arrangements | 10 |
| 7.2 | Choice of tube voltage and radiation source | 16 |
| 7.3 | Detector systems and metal screens | 18 |
| 7.4 | Alignment of beam | 20 |
| 7.5 | Reduction of scattered radiation | 20 |
| 7.6 | Source-to-object distance | 22 |
| 7.7 | Geometric magnification technique | 25 |
| 7.8 | Maximum area for a single exposure | 26 |
| 7.9 | Processing | 26 |
| 7.10 | Monitor viewing conditions and storage of digital radiographs | 27 |
| 8 | Examination report | 28 |
| Annex A (normative) | Recommended number of exposures which give an acceptable examination of a circumferential butt weld | 30 |
| Annex B (normative) | Minimum image quality values | 35 |
| Annex C (normative) | Determination of basic spatial resolution | 41 |
| Annex D (normative) | Determination of minimum grey values for CR practice | 45 |
| Annex E (informative) | Grey values, general remarks | 50 |
| Bibliography | | 52 |