

# DIN EN 31092:2013-09 (E)

**Textiles - Physiological effects - Measurement of thermal and water-vapour resistance under steady-state conditions (sweating guarded-hotplate test) (ISO 11092:1993 + Amd.1:2012) (includes Amendment :2012)**

---

## Contents

	Page
<b>Foreword.....</b>	<b>3</b>
<b>A1 Foreword to EN 31092:1993/A1:2012.....</b>	<b>3</b>
<b>Introduction .....</b>	<b>4</b>
<b>1 Scope .....</b>	<b>5</b>
<b>2 Definitions .....</b>	<b>5</b>
<b>3 Symbols and units .....</b>	<b>6</b>
<b>4 Principle.....</b>	<b>6</b>
<b>5 Apparatus .....</b>	<b>7</b>
<b>6 Test specimens .....</b>	<b>9</b>
<b>6.1 Materials <math>\leq</math> 5 mm thick .....</b>	<b>9</b>
<b>6.2 Materials <math>&gt;</math> 5 mm thick .....</b>	<b>9</b>
<b>7 Test procedure .....</b>	<b>10</b>
<b>7.1 Determination of apparatus constants .....</b>	<b>10</b>
<b>7.1.1 Determination of <math>R_{ct0}</math> .....</b>	<b>10</b>
<b>7.1.2 Determination of <math>R_{et0}</math> .....</b>	<b>10</b>
<b>7.1.3 Reference material.....</b>	<b>10</b>
<b>7.1.4 Recalibration .....</b>	<b>10</b>
<b>7.2 Assembly of test specimens on the measuring unit.....</b>	<b>10</b>
<b>7.3 Measurement of thermal resistance <math>R_{ct}</math>.....</b>	<b>11</b>
<b>7.4 Measurement of water-vapour resistance <math>R_{et}</math>.....</b>	<b>11</b>
<b>8 Precision of results.....</b>	<b>11</b>
<b>8.1 Repeatability.....</b>	<b>11</b>
<b>8.2 Reproducibility.....</b>	<b>12</b>
<b>9 Test report .....</b>	<b>12</b>
<b>Annex A (normative) Mounting procedure for specimens containing loose filling materials or having uneven thickness .....</b>	<b>13</b>
<b>Annex B (normative) Determination of corrections terms for heating power .....</b>	<b>14</b>
<b>A1 Annex C (informative) Guidance on test specimen assembly for materials prone to swelling.....</b>	<b>15</b>
<b>C.1 General.....</b>	<b>15</b>
<b>C.2 Additional guidance for a test specimen assembly for materials prone to swelling .....</b>	<b>15</b>