

DIN EN 31092:2013-09 (E)

Textiles - Physiological effects - Measurement of thermal and water-vapour resistance under steady-state conditions (sweating guarded-hotplate test) (ISO 11092:1993 + Amd.1:2012) (includes Amendment :2012)

Contents

Page

| | |
|--|-----------|
| Foreword..... | 3 |
| [A1] Foreword to EN 31092:1993/A1:2012..... | 3 |
| Introduction | 4 |
| 1 Scope | 5 |
| 2 Definitions | 5 |
| 3 Symbols and units | 6 |
| 4 Principle | 6 |
| 5 Apparatus | 7 |
| 6 Test specimens | 9 |
| 6.1 Materials \leq 5 mm thick | 9 |
| 6.2 Materials $>$ 5 mm thick | 9 |
| 7 Test procedure | 10 |
| 7.1 Determination of apparatus constants | 10 |
| 7.1.1 Determination of R_{ct0} | 10 |
| 7.1.2 Determination of R_{et0} | 10 |
| 7.1.3 Reference material | 10 |
| 7.1.4 Recalibration | 10 |
| 7.2 Assembly of test specimens on the measuring unit | 10 |
| 7.3 Measurement of thermal resistance R_{ct} | 11 |
| 7.4 Measurement of water-vapour resistance R_{et} | 11 |
| 8 Precision of results | 11 |
| 8.1 Repeatability | 11 |
| 8.2 Reproducibility | 12 |
| 9 Test report | 12 |
| Annex A (normative) Mounting procedure for specimens containing loose filling materials or having uneven thickness | 13 |
| Annex B (normative) Determination of corrections terms for heating power | 14 |
| [A1] Annex C (informative) Guidance on test specimen assembly for materials prone to swelling | 15 |
| C.1 General | 15 |
| C.2 Additional guidance for a test specimen assembly for materials prone to swelling | 15 |