ISO 8311:2013-12 (E)

Refrigerated hydroca rbon and non-petroleum based liquefied gaseous fuels - Calibration of membrane tanks and independent prismatic tanks in ships - Manual and internal electro-optical distance-ranging methods

Contents

Page

Foreword iv

Introduction v

1 Scope 1

2 Normative references 1

3 Terms and definitions 1

4 Precautions 3
4.1 General 3
4.2 Ship's condition during calibration 3
4.3 Tank distortion 3
4.4 Comparison with drawings 4
4.5 Measurements by measuring tape 4
4.6 Measurements by electro-optical distance-ranging (EODR) instrument 4
4.7 Condition of membrane 5
4.8 Safety precautions for work in membrane tanks 5

5 Equipment 5

6 Determination of measuring points 6

7 Calibration by manual method 6
7.1 General 6
7.2 Tank length measurement 7
7.3 Tank width measurement 9
7.4 Tank height measurement 12
7.5 Measurement of bottom undulation and gauge reference height 14
7.6 Correction for temperature 15

8 Calibration by electro-optical distance-ranging (EODR) method 16
8.1 General 16
8.2 Setting up of EODR instrument 16
8.3 Calibration procedure 17

9 Additional measurements 19
9.1 Location of level gauge 19
9.2 Deadwood 19

10 Calculation 19
10.1 General 19
10.2 Calculation of tank volume 20
10.3 Effect of bottom undulation 20
10.4 Area of chamfer portion 20
10.5 Trim corrections 21
10.6 List corrections 21
10.7 Combined trim and list corrections 21

10.8 Correction for tank shell expansion or contraction 21

11 Report and tables 22

12 Recalibration 23

Annex A (informative) Uncertainty associated with tank calibration 24

Annex B (informative) Example of tank capacity table (Tank No.3) 36

Annex C (informative) Example of trim correction table (Tank No. 1) 38

Annex D (informative) Example of list correction table (Tank No. 1) 40

Bibliography 42