

DIN EN ISO 13934-2:2014-06 (E)

Textiles - Tensile properties of fabrics - Part 2: Determination of maximum force using the grab method (ISO 13934-2:2014)

| Contents | Page |
|--|-------------|
| Foreword | 3 |
| Introduction | 4 |
| 1 Scope | 5 |
| 2 Normative references | 5 |
| 3 Terms and definitions | 5 |
| 4 Principle | 6 |
| 5 Sampling | 6 |
| 6 Apparatus | 6 |
| 7 Atmosphere for conditioning and testing | 7 |
| 8 Preparation of test specimens | 7 |
| 8.1 General | 7 |
| 8.2 Dimensions | 8 |
| 8.3 Preparation of test specimens | 8 |
| 8.4 Wet test specimens | 8 |
| 9 Procedure | 8 |
| 9.1 Gauge length | 8 |
| 9.2 Rate of extension | 8 |
| 9.3 Mounting of test specimens | 8 |
| 9.4 Operation | 8 |
| 9.5 Tests on wet test specimens | 9 |
| 10 Calculation and expression of results | 9 |
| 11 Test report | 9 |
| Annex A (informative) Suggested procedure for sampling | 10 |
| Annex B (informative) Locations of test specimens cut from a laboratory sample | 11 |
| Annex C (informative) Arrangements of jaws for the grab test | 12 |
| Bibliography | 13 |