DIN EN ISO 16827:2014-06 (E)

Non-destructive testing - Ultrasonic testing - Characterization and sizing of discontinuities (ISO 16827:2012)

Contents

Page

Foreword 4

Introduction 5

1 Scope 6

2 Normative references 6

3 Principles of characterization of discontinuities 6
3.1 General 6
3.2 Requirements for surface condition 7

4 Pulse echo techniques 7
4.1 General 7
4.2 Location of discontinuity 7
4.3 Orientation of discontinuity 7
4.4 Assessment of multiple indications 8
4.5 Shape of discontinuity 8
4.5.1 Simple classification 8
4.5.2 Detailed classification of shape 9
4.6 Maximum echo height of indication 9
4.7 Size of discontinuity 9
4.7.1 General 9
4.7.2 Maximum echo height techniques 9
4.7.3 Probe movement sizing techniques 10
4.7.4 Selection of sizing techniques 10
4.7.5 Sizing techniques with focussing ultrasonic probes 11
4.7.6 Use of mathematical algorithms for sizing 11
4.7.7 Special sizing techniques 11

5 Transmission technique 12
5.1 General 12
5.2 Location of discontinuity 12
5.3 Evaluation of multiple discontinuities 12
5.4 Reduction of signal amplitude 13
5.5 Sizing of discontinuity 13

Annex A (normative) Analysis of multiple indications 17

A.1 Lateral characterisation 17
A.2 Transverse (Through-thickness) characterisation 17
A.3 Shadow technique 17

Annex B (normative) Techniques for the classification of discontinuity shape 19

B.1 Simple classification 19
B.1.1 General 19
B.1.2 Reconstruction technique 19
B.1.3 Echo envelope technique 19
B.2 Detailed classification 19
B.2.1 General 19

B.2.2 Echodynamic pattern technique 20
B.2.3 Directional reflectivity 22
B.3 Combination of data 22

Annex C (informative) Maximum echo height sizing technique 30

C.1 Distance-gain-size (DGS) technique 30
C.1.1 Principle 30
C.1.2 Applications and limitations 30
C.2 Distance-amplitude-correction (DAC) curve technique 30
C.2.1 Principle 30
C.2.2 Applications and limitations 31

Annex D (normative) Probe movement sizing techniques 32

D.1 Fixed amplitude level techniques 32
D.1.1 Principle 32
D.1.2 Application and limitations 32
D.2 6 dB drop from maximum technique 32
D.2.1 Principle 32
D.2.2 Application and limitations 32
D.3 12 dB or 20 dB drop from maximum technique 33
D.3.1 Principle 33
D.3.2 Application and limitations 33
D.4 Drop to noise level technique 33
D.4.1 Principle 33
D.4.2 Application and limitations 33
D.5 6 dB drop tip location technique 34
D.5.1 Principle 34
D.5.2 Application and limitations 34
D.6 Beam axis tip location technique 34
D.6.1 Principle 34
D.6.2 Application and limitations 34
D.7 20 dB drop tip location technique 35
D.7.1 Principle 35
D.7.2 Application and limitations 35

Annex E (normative) Iterative sizing technique 44

E.1 Scope 44
E.2 Normal incidence testing 44
E.2.1 Principle 44
E.2.2 Adjustment of gain 44
E.2.3 Procedure 44
E.3 Oblique incidence testing 45

Annex F (normative) Mathematical algorithms for the estimation of the actual size of a Discontinuity 50

F.1 Large planar discontinuities 50
F.2 Small planar discontinuities 51
F.3 Planar discontinuities in a cylindrical test object 53

Annex G (informative) Examples of special sizing techniques 55

G.1 Tip diffraction techniques 55
G.2 Synthetic aperture focussing technique (SAFT) 56