

DIN EN ISO 16827:2014-06 (E)

Non-destructive testing - Ultrasonic testing - Characterization and sizing of discontinuities (ISO 16827:2012)

Contents	Page
Foreword	4
Introduction	5
1 Scope	6
2 Normative references	6
3 Principles of characterization of discontinuities	6
3.1 General	6
3.2 Requirements for surface condition	7
4 Pulse echo techniques	7
4.1 General	7
4.2 Location of discontinuity	7
4.3 Orientation of discontinuity	7
4.4 Assessment of multiple indications	8
4.5 Shape of discontinuity	8
4.5.1 Simple classification	8
4.5.2 Detailed classification of shape	9
4.6 Maximum echo height of indication	9
4.7 Size of discontinuity	9
4.7.1 General	9
4.7.2 Maximum echo height techniques	9
4.7.3 Probe movement sizing techniques	10
4.7.4 Selection of sizing techniques	10
4.7.5 Sizing techniques with focussing ultrasonic probes	11
4.7.6 Use of mathematical algorithms for sizing	11
4.7.7 Special sizing techniques	11
5 Transmission technique	12
5.1 General	12
5.2 Location of discontinuity	12
5.3 Evaluation of multiple discontinuities	12
5.4 Reduction of signal amplitude	13
5.5 Sizing of discontinuity	13
Annex A (normative) Analysis of multiple indications	17
A.1 Lateral characterisation	17
A.2 Transverse (Through-thickness) characterisation	17
A.3 Shadow technique	17
Annex B (normative) Techniques for the classification of discontinuity shape	19
B.1 Simple classification	19
B.1.1 General	19
B.1.2 Reconstruction technique	19
B.1.3 Echo envelope technique	19
B.2 Detailed classification	19
B.2.1 General	19

B.2.2	Echodynamic pattern technique	20
B.2.3	Directional reflectivity	22
B.3	Combination of data	22
Annex C (informative) Maximum echo height sizing technique		30
C.1	Distance-gain-size (DGS) technique	30
C.1.1	Principle	30
C.1.2	Applications and limitations	30
C.2	Distance-amplitude-correction (DAC) curve technique	30
C.2.1	Principle	30
C.2.2	Applications and limitations	31
Annex D (normative) Probe movement sizing techniques		32
D.1	Fixed amplitude level techniques	32
D.1.1	Principle	32
D.1.2	Application and limitations	32
D.2	6 dB drop from maximum technique	32
D.2.1	Principle	32
D.2.2	Application and limitations	32
D.3	12 dB or 20 dB drop from maximum technique	33
D.3.1	Principle	33
D.3.2	Application and limitations	33
D.4	Drop to noise level technique	33
D.4.1	Principle	33
D.4.2	Application and limitations	33
D.5	6 dB drop tip location technique	34
D.5.1	Principle	34
D.5.2	Application and limitations	34
D.6	Beam axis tip location technique	34
D.6.1	Principle	34
D.6.2	Application and limitations	34
D.7	20 dB drop tip location technique	35
D.7.1	Principle	35
D.7.2	Application and limitations	35
Annex E (normative) Iterative sizing technique		44
E.1	Scope	44
E.2	Normal incidence testing	44
E.2.1	Principle	44
E.2.2	Adjustment of gain	44
E.2.3	Procedure	44
E.3	Oblique incidence testing	45
Annex F (normative) Mathematical algorithms for the estimation of the actual size of a Discontinuity		50
F.1	Large planar discontinuities	50
F.2	Small planar discontinuities	51
F.3	Planar discontinuities in a cylindrical test object	53
Annex G (informative) Examples of special sizing techniques		55
G.1	Tip diffraction techniques	55
G.2	Synthetic aperture focussing technique (SAFT)	56