

# ISO 124:2014-03 (E)

## Latex, rubber - Determination of total solids content

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Principle .....</b>	<b>1</b>
<b>4</b>	<b>Apparatus .....</b>	<b>1</b>
<b>5</b>	<b>Sampling .....</b>	<b>1</b>
<b>6</b>	<b>Procedure .....</b>	<b>2</b>
<b>6.1</b>	<b>General .....</b>	<b>2</b>
<b>6.2</b>	<b>Heating at atmospheric pressure (70 °C and 105 °C) -- Natural and synthetic rubber latex ..</b>	<b>2</b>
<b>6.3</b>	<b>Heating at atmospheric pressure (up to 160 °C) -- Synthetic rubber latex .....</b>	<b>2</b>
<b>6.4</b>	<b>Heating at reduced pressure -- Synthetic rubber latex .....</b>	<b>2</b>
<b>7</b>	<b>Expression of results .....</b>	<b>3</b>
<b>8</b>	<b>Precision .....</b>	<b>3</b>
<b>9</b>	<b>Test report .....</b>	<b>3</b>
<b>Annex A (informative) Drying conditions for synthetic latices at atmospheric pressure .....</b>		<b>4</b>
<b>Annex B (informative) Precision statement .....</b>		<b>5</b>
<b>Bibliography .....</b>		<b>8</b>