ISO 18560-1:2014-11 (E)

Fine ceramics (advanced ceramic s, advanced technical ceramics) - Test method for air-purification performance of semiconducting photocatalytic materials by test chamber method under indoor lighting environment - Part 1: Removal of formaldehyde

Contents

Page

Foreword iv

1 Scope 1

2 Normative references 1

3 Terms and definitions 2

4 Symbols 3

5 Principle 4

6 Apparatus 4
6.1 General 4
6.2 Test chamber 5
6.3 Sealing material for test specimens 5
6.4 Air purifier 5
6.5 Supply air spiked with formaldehyde 6
6.6 Temperature and humidity controls 6
6.7 Air flow meter 6
6.8 Light source and UV sharp cut-off filter 6
6.9 Air sampling devices 6
6.10 Device to circulate air and control of air velocity 6
6.11 Analytical instrument 7

7 Test conditions 7
7.1 General 7
7.2 Test conditions of removal performance 7
7.3 Factors affecting the removal performance (optional) 8

8 Verification of test conditions 9
8.1 Monitoring of test conditions 9
8.2 Air-tightness of test chamber 9
8.3 Air change rate in test chamber 9
8.4 Efficiency of the internal test chamber air mixing 9
8.5 Recovery 9

9 Preparation of test chamber 9

10 Test specimen 10
10.1 Preparation of test specimen 10
10.2 Preparation for the test 10

11 Test methods 10
11.1 Background concentration and supply air spiked with formaldehyde 10
11.2 Placing the test specimen in the test chamber 10
11.3 Test under dark condition 10
11.4 Test for removal performance 11

11.5 Factors affecting the removal performance 11
11.6 Air sampling 11

12 Determination of formaldehyde 11

13 Calculation and expression of results 11

14 Test report 12

Annex A (informative) Example of a test chamber 14

Bibliography 17