DIN EN 15572:2015-12 (E)

Machines and plants for mining and tooling of natural stone - Safety - Requirements for edge finishing machines

Contents

Page

European foreword 4

Introduction 5

1 Scope 6

2 Normative references 7

3 Terms and definitions 8

4 List of significant hazards 18

5 Safety requirements and/or protective measures 20
5.1 General 20
5.2 Controls 20
5.3 Protection against mechanical hazards 26
5.4 Protections against no mechanical hazards 31

6 Information for use 34
6.1 Signals and warning devices 34
6.2 Marking 34
6.3 Instruction handbook 35

Annex A (normative) Noise emission measurement 39

A.1 Introduction 39
A.2 Measurement of the A-weighted emission sound pressure level at the operator positions or other specified positions 39
A.3 Determination of sound power level 40
A.4 Installation, mounting and operating conditions for noise emission measurement 44
A.5 Information to be recorded and reported 44
A.6 Declaration and verification of noise emission values 56

Annex ZA (informative) Relationship between this European standard and the essential requirements of EU Directive 2006/42/EC 58

Bibliography 59

Figures Figure 1 -- Example of a table edge finishing machine with a single work spindle 9

Figure 2 -- Example of a table edge finishing machine with more work spindles 10

Figure 3 -- Example of a vertical belt edge finishing machine 11

Figure 4 -- Example of a horizontal belt edge finishing machine 12

Figure 5 -- Example of grinding and polishing tools 13

Figure 6 -- Example of a bush-hammering tool 13

Figure 7 -- Example of a diamond wheel 14

Figure 8 -- Example of a calibrating tool 14

Figure 9 -- Example of a dripstone tool 14

DINEN15572:2015-12 Figure 10 -- Example of a cutting tool 15

Figure 11 -- Example of a shaping tool 15

Figure 12 -- Example of types of oscillating spindles-holding beam for horizontal belt edge finishing machine with oscillation range of 180° (A) and with maximum oscillation range of 5°-10° (B) 16

Figure 13 -- Example of types of oscillating spindles-holding beam for vertical belt edge finishing machine with oscillation range of 180° (A) and with maximum oscillation range of 5°-10° (B) 17

Figure 14 -- Example of a control panel holder device for horizontal belt edge finishing machine 21

Figure 15 -- Safety distance between conveyor belt and fixed guards over winding and unwinding points 30

Figure A.1 -- Measurement surface and microphone positions 42

Figure A.2 -- Example of microphone positions when the A-weighted emission sound pressure level at the operator position exceeds 80 dB and at least a dimension (L1 or L2 or L3) exceeds 7 m 43

Tables Table 1 -- List of significant hazards 18

Table 2 -- Light alloy guard thickness and tensile strength 31

Table A.1 -- Noise test code - General Data Sheet 45