

# ISO 18067:2015-05 (E)

## Textiles - Synthetic filament yarns - Determination of shrinkage in dry-hot air (after treatment)

---

| <b>Contents</b>       |  | <b>Page</b> |
|-----------------------|--|-------------|
| Foreword .....        |  | iv          |
| 1                     | Scope .....  | 1           |
| 2                     | Normative references .....                                       | 1           |
| 3                     | Terms and definition .....                                       | 1           |
| 4                     | Principle .....  | 1           |
| 5                     | Apparatus and materials .....                                    | 1           |
| 6                     | Sampling and preparation of the test specimen .....              | 2           |
| 6.1                   | Sampling .....   | 2           |
| 6.2                   | Preconditioning and conditioning .....                           | 3           |
| 6.3                   | Preparation of the test specimen .....                           | 3           |
| 6.3.1                 | Skein method .....   | 3           |
| 6.3.2                 | Single-end method .....  | 4           |
| 6.4                   | Number of specimens .....  | 4           |
| 7                     | Testing conditions .....   | 4           |
| 7.1                   | Dry-hot air treatment conditions .....                           | 4           |
| 7.2                   | Tension for the test specimen .....                              | 4           |
| 7.3                   | Equilibrium time for test specimen after thermal treatment ..... | 5           |
| 8                     | Testing procedure .....  | 5           |
| 8.1                   | Skein method A (Manual measurement) .....                        | 5           |
| 8.1.1                 | Measuring the initial length of the test specimens .....         | 5           |
| 8.1.2                 | Thermal treatment of the test specimens .....                    | 5           |
| 8.1.3                 | Equilibrium after thermal treatment .....                        | 5           |
| 8.1.4                 | Measuring the length of the test specimens after treatment ..... | 6           |
| 8.2                   | Skein method B (Automatic measurement) .....                     | 6           |
| 8.2.1                 | Measuring the initial length of the test specimens .....         | 6           |
| 8.2.2                 | Thermal treatment of the test specimens .....                    | 6           |
| 8.2.3                 | Equilibrium after thermal treatment .....                        | 6           |
| 8.2.4                 | Measuring the length of the test specimens after treatment ..... | 6           |
| 8.3                   | Single-end method .....  | 6           |
| 8.3.1                 | Measuring the initial length of the test specimens .....         | 6           |
| 8.3.2                 | Thermal treatment of the test specimens .....                    | 6           |
| 8.3.3                 | Equilibrium after thermal treatment .....                        | 6           |
| 8.3.4                 | Measuring the length of the test specimens after treatment ..... | 7           |
| 9                     | Calculation and expression of results .....                      | 7           |
| 9.1                   | Calculation .....  | 7           |
| 9.2                   | Precision .....  | 7           |
| 10                    | Test report .....  | 7           |
| Annex A (informative) | Precision experiments .....                                      | 8           |
| Bibliography .....    |  | 9           |