

ISO 11775:2015-10 (E)

Surface chemical analysis - Scanning-probe microscopy - Determination of cantilever normal spring constants

| Contents | | Page |
|-----------------------|---|-------------|
| Foreword | | iv |
| Introduction | | v |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 1 |
| 4 | Symbols and abbreviated terms | 2 |
| 5 | General information | 4 |
| 5.1 | Background information | 4 |
| 5.2 | Methods for the determination of AFM normal spring constant | 5 |
| 6 | Dimensional methods to determine k_z | 5 |
| 6.1 | General | 5 |
| 6.2 | k_z using formulae requiring 3D geometric information | 5 |
| 6.2.1 | Method | 5 |
| 6.2.2 | Measuring the required dimensions and material properties of the cantilever | 7 |
| 6.2.3 | Determining k_z for the rectangular cantilever | 8 |
| 6.2.4 | Determining k_z for the V-shaped cantilever | 8 |
| 6.2.5 | k_z for the trapezoidal cross-sections | 9 |
| 6.2.6 | k_z to account for coatings | 9 |
| 6.3 | k_z using plan view dimensions and resonant frequency for rectangular tipless cantilevers | 10 |
| 6.3.1 | Determining k_z | 10 |
| 6.3.2 | Uncertainty | 11 |
| 7 | Static experimental methods to determine k_z | 11 |
| 7.1 | General | 11 |
| 7.2 | Static experimental method with a reference cantilever | 11 |
| 7.2.1 | Set-up | 11 |
| 7.2.2 | Determining k_z | 12 |
| 7.2.3 | Uncertainty | 14 |
| 7.3 | Static experimental method using a nanoindenter | 15 |
| 7.3.1 | General | 15 |
| 7.3.2 | Determining k_z for a tipped or tipless cantilever | 15 |
| 7.3.3 | Uncertainty | 16 |
| 7.4 | Measurement methods | 18 |
| 7.4.1 | Static deflection calibration | 18 |
| 8 | Dynamic experimental methods to determine k_z | 18 |
| 8.1 | General | 18 |
| 8.2 | Dynamic experimental method using thermal vibrations using AFM | 18 |
| 8.2.1 | Determining k_z | 18 |
| 8.2.2 | Uncertainty | 20 |
| Annex A (informative) | Inter-laboratory and intra-laboratory comparison of AFM cantilevers | 21 |
| Bibliography | | 24 |