

ISO 26843:2015-12 (E)

Metallic materials - Measurement of fracture toughness at impact loading rates using precracked Charpy-type test pieces

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Normative references	1
3	Symbols	1
4	Principle	3
5	Test specimens	5
6	Testing machines	6
7	Test procedures and measurements	6
7.1	General	6
7.2	Impact velocity	7
7.3	Time to fracture	7
7.4	Multiple specimen tests	7
7.5	Single-specimen tests	7
7.6	Post-test crack length measurements	8
8	Evaluation of fracture mechanics parameters	8
9	Test report	9
9.1	Organization	9
9.2	Specimen, material, and test environment	9
9.2.1	Specimen description	9
9.2.2	Specimen dimensions	9
9.2.3	Material description	9
9.2.4	Test environment	10
9.3	Fatigue precracking conditions	10
9.4	Test data qualification	10
9.4.1	Limitations	10
9.4.2	Crack length measurements	10
9.4.3	Fracture surface appearance	10
9.4.4	Resistance curves	10
9.4.5	Checklist for data qualification	10
9.5	Test results	11
Annex A (normative)	Test machines suitable for each test procedure	12
Annex B (informative)	Estimation of strain rate	13
Annex C (normative)	Dynamic evaluation of fracture toughness	14
Annex D (normative)	Determination of resistance curves at impact loading rates by multiple specimen methods	19

Annex E (normative) Estimation of Jd-a R-curves using the normalization method	21
Annex F (normative) Determination of characteristic fracture toughness value $J_{0,2Bd}$	24
Annex G (normative) Validity criteria	25
Annex H (normative) Determination of fracture toughness in terms of J-integral	27
Annex I (informative) Example test reports	29
Bibliography	34