

ISO 21561-2:2016-03 (E)

Styrene-butadiene rubber (SBR) - Determination of the microstructure of solution-polymerized SBR - Part 2: FTIR with ATR method

| Contents | | Page |
|---|---|-------------|
| Foreword | | iv |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Principle | 1 |
| 4 | Apparatus | 2 |
| 5 | Calibration | 2 |
| 5.1 | FTIR | 2 |
| 5.2 | ATR | 2 |
| 6 | Sampling | 2 |
| 7 | Procedure for measuring ATR spectrum | 2 |
| 8 | Determination of the microstructure of butadiene and the styrene content | 3 |
| 8.1 | Measurement of the absorbance for each microstructure component | 3 |
| 8.2 | Calculation of microstructures | 4 |
| 8.2.1 | General | 4 |
| 8.2.2 | Base line correction of each absorbance peak | 5 |
| 8.2.3 | Ratio of absorbance | 5 |
| 8.2.4 | Second order terms | 5 |
| 8.2.5 | Styrene content and microstructures in mass % by regression formulae | 5 |
| 8.2.6 | Microstructures in mol % | 6 |
| 9 | Precision | 6 |
| 10 | Test report | 6 |
| Annex A (informative) Precision results from an interlaboratory test programme | | 8 |
| Annex B (informative) Acquisition of regression formulae for microstructure | | 10 |
| Annex C (informative) Determination of microstructure by NMR spectrometry | | 12 |
| Bibliography | | 16 |