

# ISO 4590:2016-07 (E)

## Rigid cellular plastics - Determination of the volume percentage of open cells and of closed cells

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
Introduction .....		v
1	Scope .....	1
2	Normative references .....	1
3	Terms and definitions .....	1
4	Principle .....	2
5	Test specimens .....	2
5.1	Number .....	2
5.2	Preparation .....	3
5.3	Dimensions .....	3
5.4	Sectioning of test specimens .....	3
6	Conditioning and test atmospheres .....	3
7	Measurement of surface area $S$ and geometrical volume $V_g$ .....	3
8	Determination of impenetrable volume $V_i$ by method 1: pressure variation (pycnometer)4	
8.1	Principle of method 1 .....	5
8.2	Description of apparatus for method 1 .....	5
8.3	Calibration of pycnometer apparatus .....	7
8.4	Procedure for method 1 .....	8
8.5	Calculation for method 1 .....	9
9	Determination of impenetrable volume $V_i$ by method 2: volume expansion .....	9
9.1	Principle of method 2 .....	9
9.2	Description of apparatus for method 2a .....	10
9.3	Calibration of apparatus for method 2a .....	11
9.4	Procedure and calculation for method 2a .....	14
9.5	Description of apparatus for method 2b .....	14
9.6	Calibration of apparatus for method 2b .....	15
9.7	Test procedure for method 2b .....	15
9.8	Test sequence for method 2b .....	16
9.9	Calculations and expression of results for method 2b .....	17
10	Correction for specimen surface cells opened during specimen preparation .....	17
10.1	For the pressure-variation method (see Clause 8) .....	17
10.2	For the volume-expansion method (see Clause 9) .....	17
11	Expression of results .....	18
11.1	Apparent volume percentage of open cells .....	18
11.2	Corrected volume percentage of open cells .....	18
12	Precision .....	19
13	Test report .....	20
Annex A (normative) Notes on procedure .....		21