

ISO 27306:2016-09 (E)

Metallic materials - Method of constraint loss correction of CTOD fracture toughness for fracture assessment of steel components

Contents		Page
Foreword		iv
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Symbols and units	3
5	Principle	3
6	Structural components of concern	4
7	Conditions for use	5
8	Assessment levels I, II, and III	6
8.1	General	6
8.2	Level I: Simplified assessment	6
8.3	Level II: Normal assessment	7
8.4	Level III: Material specific assessment	7
9	Equivalent CTOD ratio,	7
9.1	General	7
9.2	Factors influencing the equivalent CTOD ratio,	7
9.3	Procedure for calculating the equivalent CTOD ratio, , at assessment levels I to III	8
9.3.1	General	8
9.3.2	Surface crack cases (CSCP and ESCP)	8
9.3.3	Through-thickness crack cases (CTCP and ETCP)	9
Annex A (informative) Procedure for the selection of Weibull parameter, m, at level II assessment ..		17
Annex B (informative) Analytical method for the determination of Weibull parameter, m, at level III assessment		19
Annex C (informative) Guidelines for the equivalent CTOD ratio,		24
Annex D (informative) Examples of fracture assessment using the equivalent CTOD ratio,		31
Bibliography		47