

DIN EN 15657:2017-10 (E)

Acoustic properties of building elements and of buildings - Laboratory measurement of structure-borne sound from building service equipment for all installation conditions

Contents

| | Page |
|--|------|
| European foreword | 4 |
| Introduction | 5 |
| 1 Scope | 6 |
| 2 Normative references | 6 |
| 3 Terms and definitions | 7 |
| 4 Frequency range of measurement | 9 |
| 5 Installed power determination | 9 |
| 6 Direct measurement of source quantities | 11 |
| 6.1 Source free velocity squared measurement | 11 |
| 6.1.1 Measurement procedure | 11 |
| 6.1.2 Expression of the results | 11 |
| 6.2 Direct measurement of mobility (source and receiver) | 11 |
| 6.3 Source single equivalent blocked force squared | 12 |
| 6 Indirect measurement of source quantities (Reception plate method) | 12 |
| 7.1 Principle of the method | 12 |
| 7.2 Source single equivalent blocked force | 13 |
| 7.2.1 Source single equivalent blocked force squared determination | 13 |
| 7.2.2 Low mobility reception plate(s) | 13 |
| 7.2.3 Mounting of the source specimen | 14 |
| 7.3 Source single equivalent free velocity | 14 |
| 7.3.1 Source single equivalent free velocity determination | 14 |
| 7.3.2 High mobility reception plate | 15 |
| 7.3.3 Mounting of the source specimen | 15 |
| 7.4 Source single equivalent mobility | 15 |
| 8 Precision | 15 |
| 8.1 Round Robin | 15 |
| 8.2 Repeatability | 15 |
| 8.3 Reproducibility | 15 |
| 9 Expression of results | 16 |
| 10 Test report | 16 |
| Annex A (normative) List of symbols | 17 |
| Annex B (normative) Specifications for Whirlpool baths | 19 |
| B.1 Scope | 19 |
| B.2 Specifications for whirlpool baths | 19 |
| B.2.1 Mounting of the specimen | 19 |

| | | |
|--|--|----|
| B.2.2 | Operating conditions | 19 |
| B.2.3 | Expression of results | 19 |
| B.3 | Operating conditions for the tub filling phase, using a reference water jet | 19 |
| B.3.1 | General | 19 |
| B.3.2 | Specification for a defined water jet | 20 |
| B.3.3 | Test procedure | 20 |
| Annex C (normative) Power substitution method | | 22 |
| C.1 | General | 22 |
| C.2 | Principle of the method | 22 |
| C.3 | Measuring procedure | 22 |
| C.4 | Specifications for low mobility plates | 23 |
| C.5 | Specifications for high mobility plates | 23 |
| Annex D (informative) Link to models predicting structure borne sound pressure levels | | 24 |
| D.1 | General | 24 |
| D.2 | Link to EN 12354-5 | 24 |
| D.2.1 | General | 24 |
| D.2.2 | Low mobility receiver | 24 |
| D.2.3 | High mobility receiver | 25 |
| D.3 | Link to EN ISO 12354-2 | 25 |
| Annex E (informative) Reference structure borne sound power calculation | | 26 |
| E.1 | General | 26 |
| E.2 | Low mobility reference test rig | 26 |
| E.3 | High mobility reference test rig | 26 |
| Annex F (informative) Example of existing test rigs | | 27 |
| F.1 | Low mobility reception plates | 27 |
| F.2 | High mobility reception plate | 29 |
| Bibliography | | 30 |