

ISO 16809:2017-11 (E)

Non-destructive testing - Ultrasonic thickness measurement

Contents		Page
Foreword		v
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Measurement modes	1
5	General requirements	3
5.1	Instruments	3
5.2	Probes	3
5.3	Couplant	3
5.4	Reference blocks	3
5.5	Test objects	3
5.6	Qualification of personnel	4
6	Application of the technique	4
6.1	Surface conditions and surface preparation	4
6.2	Technique	4
6.2.1	General	4
6.2.2	Measurement during manufacture	5
6.2.3	In-service measurement of residual wall thickness	5
6.3	Selection of probe	6
6.4	Selection of instrument	6
6.5	Materials different from the reference material	6
6.6	Special measuring conditions	7
6.6.1	General	7
6.6.2	Measurements at temperatures below 0 °C	7
6.6.3	Measurements at elevated temperatures	7
6.6.4	Hazardous atmospheres	7
7	Instrument setting	7
7.1	General	7
7.2	Methods of setting	8
7.2.1	General	8
7.2.2	Digital thickness instruments	8
7.2.3	A-scan instrument	8
7.3	Checks of settings	9
8	Influence on accuracy	10
8.1	Operational conditions	10
8.1.1	Surface conditions	10
8.1.2	Surface temperature	10
8.1.3	Metallic coating	11
8.1.4	Non-metallic coating	11
8.1.5	Geometry	12
8.2	Equipment	12
8.2.1	Resolution	12
8.2.2	Range	13
8.3	Evaluation of accuracy	13

8.3.1	General	13
8.3.2	Influencing parameters	14
8.3.3	Method of calculation	14
9	Influence of materials	14
9.1	General	14
9.2	Inhomogeneity	14
9.3	Anisotropy	14
9.4	Attenuation	14
9.5	Surface conditions	14
9.5.1	General	14
9.5.2	Contact surface	15
9.5.3	Reflecting surface	15
9.5.4	Corrosion and erosion	15
10	Test report	16
10.1	General	16
10.2	General information	16
10.3	Measurement data	17
Annex A (informative) Corrosion in vessels and piping		18
Annex B (informative) Instrument settings		23
Annex C (informative) Parameters influencing accuracy		26
Annex D (informative) Selection of measuring technique		32
Bibliography		37