

ISO 6892-2:2018 (E)

Metallic materials — Tensile testing — Part 2: Method of test at elevated temperature

Contents

	Foreword
	Introduction
1	Scope
2	Normative references
3	Terms and definitions
4	Symbols and designations
5	Principle
6	Test piece
7	Determination of original cross-sectional area (S_0)
8	Marking the original gauge length (L_0)
9	Apparatus
10	Test conditions
10.1	Setting the force zero point
10.2	Gripping of the test piece, fixing of the extensometer and heating of the test piece, not necessarily in the following sequence
10.2.1	Method of gripping
10.2.2	Fixing of the extensometer and establishing the gauge length
10.2.2.1	General
10.2.2.2	L_e based on room temperature (Method 1)
10.2.2.3	L_e based on test temperature (Method 2)
10.2.2.3.1	Nominal L_e at test temperature (Method 2 a)
10.2.2.3.2	Reduced L_e at room temperature (Method 2 b)
10.2.2.3.3	Corrected L_e at test temperature (Method 2 c)
10.2.3	Heating of the test piece
10.3	Testing rate based on strain rate control (Method A)
10.3.1	General
10.3.2	Strain rate for the determination of the upper yield strength (R_{eH}) or proof strength properties (R_p and, if required, R_t)
10.3.3	Strain rate for the determination of the lower yield strength (R_{eL}) and percentage yield point extension (A_e), if required
10.3.4	Strain rate for the determination of the tensile strength (R_m), percentage elongation after fracture (A), percentage reduction area (Z), and, if required, percentage total extension at the maximum force (A_{gt}), percentage plastic extension at maximum force (A_g)
10.4	Method of testing with expanded strain rate ranges (Method B)
10.4.1	General
10.4.2	Rate for the determination of yield strength or proof strength properties
10.4.3	Rate for the determination of tensile strength
10.5	Choice of the method and rates
10.6	Documentation of the chosen testing conditions
11	Determination or calculation of the properties

12 Test report

13 Measurement uncertainty

14 Figures

15 Annexes

Annex A (informative) Addition to ISO 6892#1:2016, Annexes B and D

A.1 General

A.2 Test pieces for thin products: sheets, strips and flats with thickness between 0,1 mm and 3 mm

A.2.1 Test pieces to be used for sheets and flats with thickness equal to or greater than 3 mm

A.3 Test pieces to be used for wires, bars and sections with diameter or thickness equal to or greater than 4 mm

A.4 Example of test piece with collars/annular knife-edge ridges

Annex B (informative) Measurement uncertainty

Page count: 21