## ISO 48-2:2018 (E)

# Rubber, vulcanized or thermoplastic — Determination of hardness — Part 2: Hardness between 10 IRHD and 100 IRHD

### Contents

Foreword

#### Introduction

- 1 Scope
- 2 Normative references
- 3 Terms and definitions
- 4 Principle
- 5 Apparatus
  - 5.1 General
  - 5.2 Methods N, H, L and M
  - 5.3 Methods CN, CH, CL and CM
  - 5.3.1 Cylindrical surfaces of radius greater than 50 mm
  - 5.3.2 Surfaces with double curvature of large radius greater than 50 mm
  - 5.3.3 Cylindrical surfaces of radius 4 mm to 50 mm or small test pieces with double curvature
  - 5.3.4 Small O-rings and articles of radius of curvature less than 4 mm
- 6 Test pieces
  - 6.1 General
  - 6.2 Methods N, H, L and M
  - 6.2.1 General
  - 6.2.2 Thickness
  - 6.2.2.1 Methods N and H
  - 6.2.2.2 Method L
  - 6.2.2.3 Method M
  - 6.2.3 Lateral dimensions
  - 6.2.3.1 Methods N, H and L
  - 6.2.3.2 Method M
  - 6.3 Methods CN, CH, CL and CM
- 7 Time interval between forming and testing
- 8 Conditioning of test pieces
- 9 Temperature of test
- 10 Procedure
- 11 Number of readings
- 12 Expression of results
- 13 Precision
- 14 Test report

#### Annex A (informative) Empirical relationship between indentation and hardness

#### Annex B (informative) Precision results from interlaboratory test programmes

- B.1 General
- B.2 Precision results from the ITPs carried out between 1985 and 1989
- B.2.1 Programme details
- B.2.2 Precision results (1985 to 1989)
- B.3 Precision results from the ITP carried out in 2004
- B.3.1 Programme details
- B.3.2 Precision results (2004)
- B.4 Precision results from the ITP carried out in 2007
- B.4.1 Programme details
- B.4.2 Precision results (2007)
- B.5 Guidance for using precision results

Page count: 23