

ISO 17168-2:2018 (E)

Fine ceramics (advanced ceramics, advanced technical ceramics) — Test method for air-purification performance of semiconducting photocatalytic materials under indoor lighting environment — Part 2: Removal of acetaldehyde

Contents

| | |
|---------|--|
| | Foreword |
| | Introduction |
| 1 | Scope |
| 2 | Normative references |
| 3 | Terms and definitions |
| 4 | Symbols |
| 5 | Principle |
| 6 | Apparatus |
| 6.1 | Test equipment |
| 6.2 | Test gas supply |
| 6.3 | Photoreactor |
| 6.4 | Light source |
| 6.5 | UV sharp cut-off filter |
| 6.6 | Analytical system for acetaldehyde |
| 6.7 | Analytical system for CO ₂ |
| 7 | Test piece |
| 8 | Procedure |
| 8.1 | General aspects |
| 8.2 | Pretreatment of test piece |
| 8.3 | Preparation for the test |
| 8.4 | Pretest |
| 8.5 | Test of acetaldehyde removal and CO ₂ conversion |
| 8.6 | Test of acetaldehyde removal (when CO ₂ concentration cannot be measured) |
| 9 | Calculation |
| 9.1 | Calculation method |
| 9.2 | Removal percentage and removed quantity of acetaldehyde |
| 9.3 | Conversion to CO ₂ |
| 10 | Test method for test pieces with lower performance |
| 11 | Test report |
| Annex A | (informative) Results of an interlaboratory test |