ISO 20769-2:2018 (E)

Non-destructive testing — Radiographic inspection of corrosion and deposits in pipes by X- and gamma rays — Part 2: Double wall radiographic inspection

Contents

Foreword

- 1 Scope
- 2 Normative references
- 3 Terms and definitions
- 4 Classification of radiographic techniques

5 General

- 5.1 Protection against ionizing radiation
- 5.2 Personnel qualification
- 5.3 Identification of radiographs
- 5.4 Marking
- 5.5 Overlap of films or digital images
- 5.6 Types and positions of image quality indicators (IQI)
- 5.6.1 Single wire IQI
- 5.6.2 Duplex wire IQI (digital radiographs)
- 6 Recommended techniques for making radiographs
 - 6.1 Test arrangements
 - 6.1.1 General
 - 6.1.2 Double wall single image (DWSI)
 - 6.1.3 Double wall double image (DWDI)
 - 6.1.4 Alignment of beam and film/detector
 - 6.2 Choice of radiation source
 - 6.3 Film systems and screens
 - 6.4 Screens and shielding for imaging plates (computed radiography only)
 - 6.5 Reduction of scattered radiation
 - 6.5.1 Filters and collimators
 - 6.5.2 Interception of back scattered radiation
 - 6.6 Source-to-detector distance
 - 6.6.1 Double wall single image
 - 6.6.2 Double wall double image
 - 6.7 Axial coverage and overlap
 - 6.8 Circumference coverage
 - 6.8.1 General
 - 6.8.2 DWSI
 - 6.8.3 DWDI

7

- 6.9 Selection of digital radiographic equipment
- 6.9.1 General
- 6.9.2 CR systems
- 6.9.3 DDA systems

Radiograph/digital image sensitivity, quality and evaluation

- 7.1 Minimum image quality values
- 7.1.1 Wire image quality indicators
- 7.1.2 Duplex wire IQIs (digital radiographs)
- 7.1.3 Minimum normalized signal to noise ratio (digital radiographs)
- 7.2 Density of film radiographs
- 7.3 Film processing
- 7.4 Film viewing conditions

- 8 Measurement of differences in penetrated thickness
 - 8.1 Principle of technique
 - Measurement of attenuation coefficient 8.2
 - 8.3 Source and detector positioning
 - 8.4 Image grey level profiles
 - Validation 8.5
 - Key points 8.6
- 9 Digital image recording, storage, processing and viewing
 - 9.1 Scan and read out of image
 - 9.2 Calibration of DDAs
 - 9.3 Bad pixel interpolation
 - 9.4 Image processing
 - Digital image recording and storage Monitor viewing conditions 9.5
 - 9.6
- 10 **Test report**
- Annex A (normative) Minimum image quality values
- Annex B (normative) Penetrated thickness measurements from image grey levels
- (normative) Determination of basic spatial resolution Annex C

Page count: 30