ISO 8332:2018 (E)

Rubber compounding ingredients — Sulfur — Methods of test

Contents

Foreword

Introduction

1 Scope

2 Normative references

3 Terms and definitions

4 Physical and chemical properties

5 Determination of total sulfur content

5.1 Principle
5.2 Reagents
5.3 Procedure
5.4 Expression of results
5.5 Precision

6 Determination of sieve residue

6.1 Principle
6.2 Method A
6.2.1 Apparatus
6.2.2 Procedure
6.2.3 Expression of results
6.3 Method B
6.3.1 Apparatus
6.3.2 Procedure
6.3.3 Expression of results
6.3.4 Precision

7 Determination of oil content of oil-treated sulfur

7.1 Principle
7.2 Hexane procedure
7.2.1 Reagents
7.2.2 Procedure
7.2.3 Expression of results
7.3 Sulfur-saturated hexane procedure
7.3.1 Reagents
7.3.2 Procedure
7.3.3 Expression of results

8 Determination of insoluble-sulfur content

8.1 Principle
8.2 Reference procedure using toluene
8.2.1 Reagents
8.2.2 Procedure
8.2.3 Expression of results
8.3 Alternative procedure using carbon disulfide
8.3.1 Reagents
8.3.2 Procedure
8.3.3 Expression of results

9 Determination of thermal reversion of insoluble sulfur

9.1 General
9.2 Method A
9.2.1 Principle
9.2.2 Apparatus
9.2.3 Reference procedure
9.2.3.1 Reagents
9.2.3.2 Procedure
9.2.4 Alternative procedure using carbon disulfide
9.2.4.1 Reagents
9.2.4.2 Procedure
9.2.5 Expression of results
9.3 Method B
9.3.1 Principle
9.3.2 Apparatus
9.3.3 Reagents
9.3.4 Chromatographic conditions1 1 Other conditions may be used as long as the soluble sulfur peak is well resolved.
9.3.5 Preparation of calibration curve (soluble sulfur)
9.3.6 DSC programme
9.3.7 Procedure for initial soluble sulfur
9.3.8 Procedure for soluble sulfur after 10-min exposure time
9.3.9 Expression of results
9.4 Precision

10 Determination of loss in mass at 80 °C

10.1 Principle
10.2 Apparatus
10.3 Procedure
10.3.1 Method A
10.3.2 Method B
10.4 Expression of results
10.5 Precision

11 Determination of ash at 850 °C to 900 °C

11.1 Principle
11.2 Apparatus
11.3 Procedure
11.4 Expression of results
11.5 Precision

12 Determination of acidity

13 Determination of arsenic content

14 Test report

Annex A (informative) Typical values of the properties of sulfur used as a rubber compounding ingredient

A.1 Soluble (rhombic) sulfur
A.2 Insoluble (amorphous) sulfur

Annex B (informative) Precision

B.1 General
B.2 Precision details
B.2.1 Determination of thermal reversion of insoluble sulfur
B.2.2 Determination of total sulfur content, sieve residue, loss in mass and ash
B.3 Precision results
B.3.1 Determination of thermal reversion of insoluble sulfur
B.3.2 Determination of total sulfur content
B.3.3 Determination of sieve residue using method B
B.3.4 Determination of loss in mass at 80 °C using method A
B.3.5 Determination of ash at 850 °C to 900 °C

Page count: 26