

# DIN EN ISO 13588:2019-07 (E)

## Non-destructive testing of welds - Ultrasonic testing - Use of automated phased array technology (ISO 13588:20 19)

---

<b>Contents</b>		<b>Page</b>
European foreword.....		4
Foreword .....		5
<b>1</b>	<b>Scope.....</b>	<b>6</b>
<b>2</b>	<b>Normative references.....</b>	<b>6</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>7</b>
<b>4</b>	<b>Testing levels.....</b>	<b>7</b>
<b>5</b>	<b>Information required prior to testing.....</b>	<b>9</b>
<b>5.1</b>	<b>Items to be defined prior to procedure development .....</b>	<b>9</b>
<b>5.2</b>	<b>Specific information required by the operator before testing .....</b>	<b>9</b>
<b>5.3</b>	<b>Written test procedure .....</b>	<b>10</b>
<b>6</b>	<b>Requirements for personnel and test equipment.....</b>	<b>10</b>
<b>6.1</b>	<b>Personnel qualifications.....</b>	<b>10</b>
<b>6.2</b>	<b>Test equipment.....</b>	<b>11</b>
<b>6.2.1</b>	<b>General.....</b>	<b>11</b>
<b>6.2.2</b>	<b>Ultrasonic instrument .....</b>	<b>11</b>
<b>6.2.3</b>	<b>Ultrasonic probes.....</b>	<b>11</b>
<b>6.2.4</b>	<b>Scanning mechanisms .....</b>	<b>11</b>
<b>7</b>	<b>Preparation for testing.....</b>	<b>11</b>
<b>7.1</b>	<b>Volume to be tested.....</b>	<b>11</b>
<b>7.2</b>	<b>Verification of the test setup .....</b>	<b>11</b>
<b>7.3</b>	<b>Scan increment setting.....</b>	<b>11</b>
<b>7.4</b>	<b>Geometry considerations.....</b>	<b>12</b>
<b>7.5</b>	<b>Preparation of scanning surfaces.....</b>	<b>12</b>
<b>7.6</b>	<b>Temperature.....</b>	<b>12</b>
<b>7.7</b>	<b>Couplant.....</b>	<b>12</b>
<b>8</b>	<b>Testing of base material .....</b>	<b>12</b>
<b>9</b>	<b>Range and sensitivity settings.....</b>	<b>13</b>
<b>9.1</b>	<b>Settings.....</b>	<b>13</b>
<b>9.1.1</b>	<b>General.....</b>	<b>13</b>
<b>9.1.2</b>	<b>Pulse-echo time window.....</b>	<b>13</b>
<b>9.1.3</b>	<b>Pulse-echo sensitivity settings .....</b>	<b>13</b>
<b>9.1.4</b>	<b>TOFD settings.....</b>	<b>13</b>
<b>9.2</b>	<b>Checking of the settings .....</b>	<b>13</b>
<b>9.3</b>	<b>Reference blocks .....</b>	<b>14</b>
<b>9.3.1</b>	<b>General.....</b>	<b>14</b>
<b>9.3.2</b>	<b>Material.....</b>	<b>14</b>
<b>9.3.3</b>	<b>Dimensions and shape .....</b>	<b>14</b>
<b>9.3.4</b>	<b>Reference reflectors.....</b>	<b>14</b>
<b>10</b>	<b>Equipment checks.....</b>	<b>15</b>
<b>11</b>	<b>Procedure qualification .....</b>	<b>15</b>

<b>12</b>	<b>Weld testing.....</b>	<b>15</b>
<b>13</b>	<b>Data storage.....</b>	<b>16</b>
<b>14</b>	<b>Interpretation and analysis of phased array data .....</b>	<b>16</b>
<b>14.1</b>	<b>General .....</b>	<b>16</b>
<b>14.2</b>	<b>Assessing the quality of the phased array data.....</b>	<b>16</b>
<b>14.3</b>	<b>Identification of relevant indications.....</b>	<b>16</b>
<b>14.4</b>	<b>Classification of relevant indications .....</b>	<b>16</b>
<b>14.5</b>	<b>Determination of location .....</b>	<b>17</b>
<b>14.6</b>	<b>Determination of length and height.....</b>	<b>17</b>
<b>14.6.1</b>	<b>General .....</b>	<b>17</b>
<b>14.6.2</b>	<b>Determination of length.....</b>	<b>17</b>
<b>14.6.3</b>	<b>Determination of height.....</b>	<b>17</b>
<b>14.7</b>	<b>Evaluation against acceptance criteria.....</b>	<b>18</b>
<b>15</b>	<b>Test report .....</b>	<b>18</b>
	<b>Annex A (informative) Typical reference blocks and reference reflectors .....</b>	<b>20</b>
	<b>Annex B (informative) Illustrations of possible signals to be used.....</b>	<b>25</b>
	<b>Bibliography .....</b>	<b>29</b>