

ISO 6158:2018 (E)

Metallic and other inorganic coatings — Electrodeposited coatings of chromium for engineering purposes

Contents

| | |
|---------|---|
| | Foreword |
| | Introduction |
| 1 | Scope |
| 2 | Normative references |
| 3 | Terms and definitions |
| 4 | Information to be supplied by the purchaser to the processor |
| 5 | Designation |
| 5.1 | General |
| 5.2 | Designation specification |
| 5.3 | Designation of basis metal |
| 5.4 | Designation of heat treatment requirements |
| 5.5 | Designation of type and thickness of metal coating |
| 5.6 | Examples of designations |
| 6 | Requirements |
| 6.1 | Special test specimens |
| 6.2 | Appearance |
| 6.3 | Surface finish |
| 6.4 | Thickness |
| 6.5 | Hardness |
| 6.6 | Adhesion |
| 6.7 | Porosity |
| 6.8 | Stress relief heat treatment prior to coating |
| 6.9 | Hydrogen-embrittlement-relief heat treatment |
| 6.10 | Peening of metal parts |
| 6.11 | Use of undercoats |
| 6.12 | Stripping |
| 6.13 | Corrosion resistance/multilayer chromium plating |
| 6.14 | Surface roughness of electroplated metallic chromium coating |
| 7 | Sampling |
| Annex A | (informative) Typical thickness of metallic chromium coatings specified in engineering applications |
| Annex B | (normative) Thickness test methods for electroplated metallic chromium and other metallic coatings |
| B.1 | General |
| B.2 | Destructive tests |
| B.2.1 | Microscopical method |
| B.2.2 | Coulometric method |
| B.2.3 | Scanning electron microscope method |
| B.3 | Non-destructive tests |
| B.3.1 | Magnetic method |
| B.3.2 | Beta backscatter method |
| B.3.3 | X-ray spectrometric method |

Annex C (normative) Determination of cracks and pores in metallic chromium coatings

C.1 General

C.2 Microscopical examination for cracks without pretreatment

C.3 Copper deposition method for cracks and pores — Copper sulfate (Dubpernell test)

C.3.1 Principle

C.3.2 Procedure

Annex D (normative) Classification of different quality/grade of roughness of electrodeposited metallic chromium coatings

Page count: 13