DIN EN 1518:2019-06 (E)

Non-destructive testing - Leak testing - Characterization of mass spectrometer leak detectors

Contents

Page

Foreword 4

1 Scope 5

2 Normative references 5

3 Definitions 5
3.1 Terms 5

4 Description of a MSLD 8
4.1 Main parts of a MSLD 8
4.2 Operating principles of MSLD 9
4.2.1 Direct flow leak detectors 9
4.2.2 Counterflow leak detectors 10
4.3 MLSD specification 10

5 Apparatus for methods of characterization 11
5.1 Leaks 11
5.1.1 Small tracer gas leaks 11
5.1.2 Large air leak 11
5.2 Leak isolation valve (see prEN 1330-8) 11
5.3 Test vessel 11
5.4 Arrangement for test 12
5.4.1 Auxiliary pumping system 12
5.4.2 Materials 12
5.5 Preparation for test 12
5.5.1 Power supply 12
5.5.2 Warming up 12
5.5.3 Adjustment 12
5.5.4 Constant pumping speed 12
5.5.5 Constant compression ratio of the high vacuum pump 12

6 Reference conditions for characterization 12
6.1 Reference temperature 12
6.2 Reference pressure 12
6.3 Reference humidity 13

7 Test procedures 13
7.1 General 13
7.2 Minimum detectable leakage rate 13
7.2.1 Background drift and noise 13
7.2.2 Auxiliary pumping system background 13
7.2.3 Sensitivity 14
7.2.4 Time constant 14
7.3 Minimum detectable concentration 14
7.3.1 Background drift and noise 15
7.3.2 Background signal 15
7.3.3 Sensitivity 16
7.4 Inlet pumping speed for tracer gas 16

8 Results 17
8.1 Minimum detectable leakage rate 17
8.1.1 Evaluation 17
8.1.2 Expression of minimum detectable leakage rate 18
8.2 Minimum detectable concentration 18
8.2.1 Evaluation 18
8.2.2 Expression of minimum detectable concentration 19
8.3 Inlet pumping speed 19
8.3.1 Evaluation 19
8.3.2 Expression of inlet pumping speed 20
9 Test report 20