

ISO 11952:2019 (E)

Surface chemical analysis — Scanning-probe microscopy — Determination of geometric quantities using SPM: Calibration of measuring systems

Contents

	Foreword
	Introduction
1	Scope
2	Normative references
3	Terms and definitions
4	Symbols
5	Characteristics of SPMs
5.1	Components of an SPM
5.2	Metrological categories of SPMs
5.3	Block diagram of an SPM
5.3.1	For category C:
5.3.2	Additionally, for category B:
5.3.3	Additionally, for category A:
5.4	Calibration interval
6	Preliminary characterization of the measuring system
6.1	Overview of the instrument characteristics and influencing factors to be investigated
6.2	Waiting times after interventions in the measuring system (e.g. instrument installation, intrinsic effects, carrying out operation, warm-up, tip/specimen change)
6.2.1	Adjustment of the instrument to ambient conditions
6.2.2	Potential causes of drift
6.2.3	Procedure
6.3	External influences
6.3.1	Sources of external influences
6.3.2	Consequences of external influences and countermeasures
6.4	Summary
7	Calibration of scan axes
7.1	General
7.2	Measurement standards ² 2 The products mentioned in this subclause are examples of suitable products available commercially. This information is given for the convenience of users of this document and does not constitute an endorsement by ISO of these products, nor are they necessarily the best products available for the purpose in question.
7.2.1	Requirements for measurement standards
7.2.2	Handling of measurement standards
7.3	Xy-scanner guidance deviations of the x- and y-axes (xtz, ytz)
7.3.1	Definition of xy-scanner guidance deviations in vertical direction (z-plane)
7.3.2	Measurement strategy
7.3.3	Flatness measurement standards
7.3.4	Measurements
7.3.5	Evaluation of results
7.3.6	Summary
7.3.7	Extended calibration measurements
7.4	Calibration of x- and y-axis (Cx, Cy) and of rectangularity (ϕ_{xy}) and determination of deviations (xtx, yty, ywx)
7.4.1	General

7.4.2	Definition of pitch p_x and p_y and rectangularity (ϕ_{xy}) in the x-y-plane
7.4.3	Measurement strategy
7.4.4	Selection of lateral measurement standards
7.4.5	Basic calibration — Adjustments and measurements
7.4.6	Extended calibrations (scan speed, angle, and eccentric measurements)
7.4.7	Evaluation
7.4.8	Extended evaluations: nonlinearity of the x-y-axis
7.4.9	Summary
7.5	Calibration of the z-axis C_z , ϕ_{xz} , and ϕ_{yz} , and determination of the deviations z_{tz} , z_{wx} , and z_{wy}
7.5.1	General
7.5.2	Definitions of the step height
7.5.3	Measurement strategy
7.5.4	Selection of step height measurement standards
7.5.5	Basic calibration — Adjustments and measurements
7.5.6	Extended calibrations
7.5.7	Evaluations
7.5.7.1	General
7.5.7.2	Profile evaluation according to ISO 5436-1
7.5.7.2.1	General
7.5.7.2.2	Alternative areal evaluation
7.5.7.3	Histogram method
7.5.7.4	Comparison of the evaluation methods
7.5.8	Summary
7.6	3D measurement standards for alternative and extended calibration
7.6.1	General
7.6.2	Requirements for 3D measurement standards
7.6.3	Selection of the 3D measurement standards
7.6.4	Carrying-out of the basic calibration
7.6.5	Evaluation of the measurements
7.6.6	Extended calibrations
7.6.6.1	Measurements
7.6.6.2	Evaluations
7.6.7	Advantages and disadvantages of the 3D measurement standard
8	Report of calibration results
8.1	General
8.2	Equipment used
8.3	Statements on ambient conditions
8.4	From Clause 5: Preliminary investigations
8.5	From Clause 5: Calibration — Details of measurement standards, scan range and scan speed
8.6	Further statements
9	Uncertainties of measurement
9.1	General
9.2	Vertical measurand (height and depth)
10	Report of results (form)
Annex A	(informative) Example of superposition of disturbing influences in the topography image
Annex B	(informative) Sound investigations: effects of a sound-proofing hood
Annex C	(informative) Thermal isolation effect of a sound-proofing hood/measuring cabin
Annex D	(informative) Handling of contaminations in recorded topography images
Annex E	(informative) Step height determination: comparison between histogram and ISO 5436-1 method
Annex F	(normative) Uncertainty of measurement for lateral measurands (pitch, position, diameter)
F.1	Lateral measurands
F.2	Model for pitch measurements