

DIN EN ISO 21968:2020-02 (E)

Non-magnetic metallic coatings on metallic and non-metallic basis materials - Measurement of coating thickness - Phase-sensitive eddy-current method (ISO 21968:2019)

Contents	Page
European foreword	3
Foreword	4
1 Scope	5
2 Normative references	5
3 Terms and definitions	5
4 Principle of measurement	6
5 Factors affecting measurement uncertainty	9
5.1 Basic influence of the coating thickness	9
5.2 Electrical properties of the coating	9
5.3 Geometry — Base material thickness	9
5.4 Geometry — Edge effects	9
5.5 Geometry — Surface curvature	10
5.6 Surface roughness	10
5.7 Lift-off effect	10
5.8 Probe pressure	12
5.9 Probe tilt	12
5.10 Temperature effects	12
5.11 Intermediate coatings	12
5.12 External electromagnetic fields	12
6 Calibration and adjustment of the instrument	12
6.1 General	12
6.2 Thickness reference standards	13
6.3 Methods of adjustment	13
7 Measurement procedure and evaluation	14
7.1 General	14
7.2 Number of measurements and evaluation	14
8 Uncertainty of the results	15
8.1 General remarks	15
8.2 Uncertainty of the calibration of the instrument	15
8.3 Stochastic errors	16
8.4 Uncertainties caused by factors summarized in Clause 5	17
8.5 Combined uncertainty, expanded uncertainty and final result	17
9 Precision	18
9.1 General	18
9.2 Repeatability (r)	18
9.3 Reproducibility limit (R)	20
10 Test report	21
Annex A (informative) Eddy-current generation in a metallic conductor	22
Annex B (informative) Basics of the determination of the uncertainty of a measurement of the used measurement method corresponding to ISO/IEC Guide 98-3	28
Annex C (informative) Basic performance requirements for coating thickness gauges based on the phase-sensitive eddy-current method described in this document	30
Annex D (informative) Examples for the experimental estimation of factors affecting the measurement accuracy	32

Annex E (informative) Table of the student factor	37
Annex F (informative) Example of uncertainty estimation.....	38
Annex G (informative) Details on precision	41
Bibliography	43