

# ISO 28763:2019-08 (E)

## Vitreous and porcelain enamels - Regenerative, enamelled and packed panels for air-gas and gas-gas heat exchangers - Specifications

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>1</b>
<b>4</b>	<b>Steel substrates .....</b>	<b>2</b>
4.1	Delivery .....	2
4.2	Analysis .....	2
4.3	Hydrogen permeability .....	2
4.4	Fish scaling test .....	2
4.5	Pickling speed .....	3
<b>5</b>	<b>Enamel frit .....</b>	<b>3</b>
5.1	Delivery .....	3
5.2	Coefficient of expansion .....	3
5.3	Fusion flow .....	3
5.4	Boiling-water (vapour phase) resistance .....	3
5.5	Acid resistance .....	3
5.6	Thermal-shock resistance .....	3
5.7	Adherence .....	4
<b>6</b>	<b>Characteristics of the enamel coating .....</b>	<b>4</b>
6.1	Adherence .....	4
6.2	Thickness .....	4
6.3	Thermal-shock resistance .....	5
6.4	Fundamental defects .....	5
6.5	Open defects .....	5
6.6	Edge covering of gas-gas heaters .....	6
6.7	Boiling sulfuric acid resistance .....	6
6.8	Rework .....	6
<b>7</b>	<b>Characteristics after packing .....</b>	<b>6</b>
7.1	Packing pressure .....	6
7.2	Visual examination .....	6
7.3	Edge covering of gas-gas heaters .....	7
<b>8</b>	<b>Documentation .....</b>	<b>7</b>
<b>Annex A (normative)</b>	<b>Method for determining thermal-shock resistance of vitreous or porcelain enamel coatings .....</b>	<b>8</b>