

DIN 53100:2020-04 (E)

Metallic coatings - Electroplated coatings of nickel plus chromium and of copper plus nickel plus chromium on plastics materials

| Contents | Page |
|------------------------------------------------------------------------------------|-------------|
| Foreword | 4 |
| Introduction | 5 |
| 1 Scope | 6 |
| 2 Normative references | 6 |
| 3 Terms and definitions..... | 6 |
| 4 Ordering details..... | 7 |
| 4.1 Essential information..... | 7 |
| 4.2 Additional information..... | 7 |
| 5 Service condition numbers | 8 |
| 6 Designation | 8 |
| 6.1 General | 8 |
| 6.2 Base material..... | 8 |
| 6.3 Metal intermediate coatings..... | 8 |
| 6.3.1 General | 8 |
| 6.3.2 Copper and nickel intermediate coatings | 8 |
| 6.4 Metal coatings..... | 9 |
| 6.4.1 General | 9 |
| 6.4.2 Nickel coatings | 9 |
| 6.4.3 Chromium coatings..... | 9 |
| 6.5 Examples of designations | 10 |
| 7 Requirements | 10 |
| 7.1 Base material..... | 10 |
| 7.2 Appearance of the coated component | 10 |
| 7.3 Thickness of copper or nickel intermediate coating | 11 |
| 7.4 Local coating thickness | 11 |
| 7.5 Thermal cycling test..... | 11 |
| 7.6 Copper accelerated salt spray test (CASS test) | 11 |
| 7.7 Combined thermal cycling test with CASS test..... | 12 |
| 7.8 STEP Test (Simultaneous Thickness and Electrode Potential determination) | 12 |
| 8 Sampling..... | 12 |
| 9 Test method | 12 |
| 10 Test report..... | 13 |
| Annex A (informative) Service condition numbers | 14 |
| Annex B (normative) Methods of determining coating thickness | 15 |
| B.1 General | 15 |
| B.2 Methods..... | 15 |
| B.2.1 Microscopic method | 15 |
| B.2.2 Coulometric method..... | 15 |
| B.2.3 X-ray spectrometric method..... | 15 |

| | |
|-------------------------------------------------------------------------------------------|-----------|
| Annex C (normative) Determination of cracks or pores in the chromium coating | 17 |
| C.1 General | 17 |
| C.2 Preparation of parts | 17 |
| C.3 Galvanostatic test (Dubpernell test) | 18 |
| C.3.1 Composition of the copper electrolyte | 18 |
| C.3.2 Working conditions | 18 |
| C.3.3 Procedure | 18 |
| C.3.4 Evaluation | 18 |
| C.4 Potentiostatic Dubpernell test [5] | 18 |
| C.4.1 Composition of the copper electrolyte | 18 |
| C.4.2 Working conditions | 18 |
| C.4.3 Procedure | 19 |
| C.4.4 Evaluation | 19 |
| C.5 Potentiostatic test (Fuhrmann test) | 19 |
| C.5.1 Set-up and description of measuring cell | 19 |
| C.5.2 Composition of the copper electrolyte | 20 |
| C.5.3 Working conditions | 20 |
| C.5.4 Procedure | 20 |
| C.5.5 Evaluation | 21 |
| C.6 Anodizing test (Fechner test [7]) | 21 |
| C.6.1 General | 21 |
| C.6.2 Composition of the electrolyte | 21 |
| C.6.3 Working conditions | 21 |
| C.6.4 Procedure | 21 |
| C.6.5 Evaluation | 22 |
| Annex D (normative) Thermal cycling test | 23 |
| D.1 General | 23 |
| D.2 Principle of method | 23 |
| D.3 Test pieces | 23 |
| D.3.1 Sampling and number of test pieces | 23 |
| D.3.2 Storage of test pieces | 23 |
| D.4 Test apparatus | 23 |
| D.5 Procedure | 24 |
| Annex E (normative) Thermal cycling test combined with CASS test | 25 |
| E.1 Principle of method | 25 |
| E.2 Procedure | 25 |
| Annex F (normative) Glacial acetic acid test | 26 |
| F.1 General | 26 |
| F.2 Reagents | 26 |
| F.3 Test apparatus | 26 |
| F.4 Procedure | 26 |
| F.5 Evaluation | 26 |
| Bibliography | 27 |

Figures

| | |
|--------------------------------------------------------------|-----------|
| Figure C.1 — Schematic set-up of measuring cell | 20 |
|--------------------------------------------------------------|-----------|

Tables

| | |
|---------------------------------------------------------------------------------|-----------|
| Table 1 — Requirements for double nickel coatings | 9 |
| Table 2 — Minimum layer thicknesses for coating systems on plastic | 11 |
| Table 3 — Requirements | 12 |
| Table D.1 — Service condition numbers and storage temperatures | 24 |