ISO 6892-1:2019-11 (E)

Metallic materials - Tensile testing - Part 1: Metho d of test at room temperature

Contents

Page

Foreword v

Introduction vi

1 Scope 1

2 Normative references 1

3 Termsanddefinitions 1

4 Symbols 6

5 Principle 8

6 Test pieces 8
6.1 Shape and dimensions 8
6.1.1 General 8
6.1.2 Machined test pieces 9
6.1.3 Unmachined test pieces 9
6.2 Types 9
6.3 Preparation of test pieces 10

7 Determination of original cross-sectional area 10

8 Original gauge length and extensometer gauge length 10
8.1 Choice of the original gauge length 10
8.2 Marking the original gauge length 10
8.3 Choice of the extensometer gauge length 11

9 Accuracy of testing apparatus 11

10 Conditions of testing 11
10.1 Setting the force zero point 11
10.2 Method of gripping 11
10.3 Testing rates 12
10.3.1 General information regarding testing rates 12
10.3.2 Testing rate based on strain rate (method A) 12
10.3.3 Testing rate based on stress rate (method B) 14
10.3.4 Report of the chosen testing conditions 15

11 Determination of the upper yield strength 16

12 Determination of the lower yield strength 16

13 Determination of proof strength, plastic extension 16

14 Determination of proof strength, total extension 17

15 Methodofverificationofpermanentsetstrength 17

16 Determination of the percentage yield point extension 17

17 Determination of the percentage plastic extension at maximum force 17

18 Determination of the percentage total extension at maximum force 18

19 Determination of the percentage total extension at fracture 18

20 Determination of percentage elongation after fracture 18

21 Determination of percentage reduction of area 19

22 Test report 20

23 Measurement uncertainty 20
23.1 General 20
23.2 Test conditions 21
23.3 Test results 21

Annex A (informative) Recommendations concerning the use of computer-controlled tensile testing machines 34

Annex B (normative) Types of test pieces to be used for thin products: sheets, strips, and flatsbetween0,1mmand3mmthick 40

Annex C (normative) Types of test pieces to be used for wire, bars, and sections with a diameterorthicknessoflessthan4mm 43

Annex D (normative)Typesoftestpiecestobeusedforsheetsandflatsofthicknessequal toorgreaterthan3mmandwire,bars,andsectionsofdiameterorthicknessequal to or greater than 4 mm 44

Annex E (normative) Types of test pieces to be used for tubes 48

Annex F (informative) Estimation of the crosshead separation rate in consideration of thestiffness(orcompliance)ofthetestingequipment 50

Annex G (normative) Determination of the modulus of elasticity of metallic materials using a uniaxial tensile test 52

Annex H (informative)Measuringthepercentageelongationafterfractureifthespecified value is less than 5 % 61

Annex I (informative) Measurement of percentage elongation after fracture based on subdivision of the original gauge length 62

Annex J (informative)Determinationofthepercentageplasticelongationwithoutnecking, Awn, for long products such as bars, wire, and rods 64

Annex K (informative) Estimation of the uncertainty of measurement 65

Annex L (informative) Precision of tensile testing -- Results from interlaboratory programmes 69

Bibliography 76