

# DIN EN 1097-8:2020-06 (E)

## Tests for mechanical and physical properties of aggregates - Part 8: Determination of the polished stone value

---

| <b>Contents</b>   |   | <b>Page</b> |
|---|---|-------------|
| <b>European foreword</b> .....  |   | <b>4</b>    |
| <b>1</b>  | <b>Scope</b> .....                                  | <b>6</b>    |
| <b>2</b>  | <b>Normative references</b> .....                   | <b>6</b>    |
| <b>3</b>  | <b>Terms and definitions</b> .....                  | <b>6</b>    |
| <b>4</b>  | <b>Principle</b> .....                              | <b>7</b>    |
| <b>5</b>  | <b>Materials</b> .....                              | <b>7</b>    |
| <b>5.1</b>  | <b>General</b> .....                                | <b>7</b>    |
| <b>5.2</b>  | <b>Materials</b> .....                              | <b>7</b>    |
| <b>6</b>  | <b>Apparatus</b> .....                              | <b>8</b>    |
| <b>6.1</b>  | <b>General</b> .....                                | <b>8</b>    |
| <b>6.2</b>  | <b>Accelerated polishing machine</b> .....          | <b>8</b>    |
| <b>6.3</b>  | <b>Friction tester</b> .....                        | <b>11</b>   |
| <b>6.4</b>  | <b>Test sieves</b> .....                            | <b>14</b>   |
| <b>6.5</b>  | <b>Grid sieve</b> .....                             | <b>14</b>   |
| <b>6.6</b>  | <b>Length gauge or callipers</b> .....              | <b>14</b>   |
| <b>6.7</b>  | <b>Equipment for preparing test specimens</b> ..... | <b>14</b>   |
| <b>7</b>  | <b>Preparation of test specimens</b> .....          | <b>15</b>   |
| <b>8</b>  | <b>Conditioning of the rubber-tyred wheel</b> ..... | <b>16</b>   |
| <b>9</b>  | <b>Accelerated polishing of specimens</b> .....     | <b>16</b>   |
| <b>10</b>   | <b>Friction test procedure</b> .....                | <b>18</b>   |
| <b>11</b>   | <b>Calculation and expression of results</b> .....  | <b>21</b>   |
| <b>12</b>   | <b>Test report</b> .....                            | <b>22</b>   |
| <b>12.1</b>   | <b>Required data</b> .....                          | <b>22</b>   |
| <b>12.2</b>   | <b>Optional data</b> .....                          | <b>22</b>   |
| <b>Annex A(normative) Determination of aggregate abrasion value (AAV)</b> ..... |   | <b>23</b>   |
| <b>A.1</b>  | <b>General</b> .....                                | <b>23</b>   |
| <b>A.2</b>  | <b>Principle</b> .....                              | <b>23</b>   |
| <b>A.3</b>  | <b>Materials</b> .....                              | <b>23</b>   |
| <b>A.4</b>  | <b>Apparatus</b> .....                              | <b>24</b>   |
| <b>A.4.1</b>  | <b>General</b> .....                                | <b>24</b>   |
| <b>A.4.2</b>  | <b>Abrasion machine</b> .....                       | <b>24</b>   |
| <b>A.4.3</b>  | <b>Test sieves</b> .....                            | <b>24</b>   |
| <b>A.4.4</b>  | <b>Grid sieve</b> .....                             | <b>24</b>   |
| <b>A.4.5</b>  | <b>Balance</b> .....                                | <b>25</b>   |
| <b>A.4.6</b>  | <b>Small fine-haired brushes</b> .....              | <b>25</b>   |
| <b>A.4.7</b>  | <b>Brush</b> .....                                  | <b>25</b>   |
| <b>A.4.8</b>  | <b>Clamp</b> .....                                  | <b>25</b>   |

|   |   |           |
|---|---|-----------|
| <b>A.5</b>  | <b>Preparation of test specimens .....</b>  | <b>25</b> |
| <b>A.5.1</b>  | <b>Test portion .....</b>   | <b>25</b> |
| <b>A.5.2</b>  | <b>Specimens .....</b>  | <b>25</b> |
| <b>A.6</b>  | <b>Procedure .....</b>  | <b>25</b> |
| <b>A.7</b>  | <b>Calculation and expression of results .....</b>  | <b>26</b> |
| <b>A.8</b>  | <b>Test report .....</b>  | <b>26</b> |
| <b>Annex B(normative) Control of materials - Corn emery and emery flour .....</b>                                     |   | <b>27</b> |
| <b>Annex C(normative) Calibration of the accelerated polishing machine .....</b>                                      |   | <b>28</b> |
| <b>C.1</b>  | <b>Control of rubber-tyred wheels .....</b>   | <b>28</b> |
| <b>C.2</b>  | <b>Accelerated polishing machine .....</b>  | <b>28</b> |
| <b>C.3</b>  | <b>Rate of flow of corn emery and emery flour .....</b>                                   | <b>30</b> |
| <b>Annex D(normative) Calibration of the friction tester and sliders .....</b>  |   | <b>31</b> |
| <b>D.1</b>  | <b>Friction tester .....</b>  | <b>31</b> |
| <b>D.1.1</b>  | <b>General .....</b>  | <b>31</b> |
| <b>D.1.2</b>  | <b>Mass of pendulum arm and pointer .....</b>   | <b>31</b> |
| <b>D.1.3</b>  | <b>Balancing of the pendulum arm assembly .....</b>                                       | <b>31</b> |
| <b>D.1.4</b>  | <b>Setting the effective spring tension .....</b>   | <b>31</b> |
| <b>D.1.5</b>  | <b>Setting the pointer stop .....</b>   | <b>31</b> |
| <b>D.2</b>  | <b>Control of sliders and slider rubber .....</b>   | <b>32</b> |
| <b>Annex E(normative) Friction tester reference stone specimen preparation and friction slider conditioning .....</b> |   | <b>33</b> |
| <b>E.1</b>  | <b>General .....</b>  | <b>33</b> |
| <b>E.2</b>  | <b>Preparation and initial testing of friction tester reference stone specimens .....</b> | <b>33</b> |
| <b>E.3</b>  | <b>Slider conditioning .....</b>  | <b>33</b> |
| <b>Annex F(informative) Precision for the aggregate abrasion value (AAV) .....</b>                                    |   | <b>34</b> |
| <b>F.1</b>  | <b>General .....</b>  | <b>34</b> |
| <b>F.2</b>  | <b>Precision values for repeatability and reproducibility .....</b>                       | <b>34</b> |
| <b>Bibliography .....</b>   |   | <b>35</b> |