

DIN EN ISO 6892-1:2020-06 (E)

Metallic materials - Tensile testing - Part 1: Method of test at room temperature (ISO 6892-1:2019)

| Contents | Page |
|--|-------------|
| European foreword | 4 |
| Foreword | 5 |
| Introduction..... | 6 |
| 1 Scope | 7 |
| 2 Normative references | 7 |
| 3 Terms and definitions | 7 |
| 4 Symbols | 12 |
| 5 Principle | 14 |
| 6 Test pieces | 14 |
| 6.1 Shape and dimensions..... | 14 |
| 6.1.1 General..... | 14 |
| 6.1.2 Machined test pieces..... | 15 |
| 6.1.3 Unmachined test pieces..... | 15 |
| 6.2 Types..... | 15 |
| 6.3 Preparation of test pieces..... | 16 |
| 7 Determination of original cross-sectional area | 16 |
| 8 Original gauge length and extensometer gauge length | 16 |
| 8.1 Choice of the original gauge length..... | 16 |
| 8.2 Marking the original gauge length..... | 17 |
| 8.3 Choice of the extensometer gauge length..... | 17 |
| 9 Accuracy of testing apparatus | 17 |
| 10 Conditions of testing | 17 |
| 10.1 Setting the force zero point..... | 17 |
| 10.2 Method of gripping..... | 17 |
| 10.3 Testing rates..... | 18 |
| 10.3.1 General information regarding testing rates..... | 18 |
| 10.3.2 Testing rate based on strain rate (method A)..... | 18 |
| 10.3.3 Testing rate based on stress rate (method B)..... | 20 |
| 10.3.4 Report of the chosen testing conditions..... | 21 |
| 11 Determination of the upper yield strength | 21 |
| 12 Determination of the lower yield strength | 22 |
| 13 Determination of proof strength, plastic extension | 22 |
| 14 Determination of proof strength, total extension | 22 |
| 15 Method of verification of permanent set strength | 23 |
| 16 Determination of the percentage yield point extension | 23 |
| 17 Determination of the percentage plastic extension at maximum force | 23 |
| 18 Determination of the percentage total extension at maximum force | 23 |
| 19 Determination of the percentage total extension at fracture | 24 |
| 20 Determination of percentage elongation after fracture | 24 |
| 21 Determination of percentage reduction of area | 25 |
| 22 Test report | 25 |

| | | |
|----------------|--|-----------|
| 23 | Measurement uncertainty | 26 |
| 23.1 | General..... | 26 |
| 23.2 | Test conditions..... | 26 |
| 23.3 | Test results..... | 26 |
| Annex A | (informative) Recommendations concerning the use of computer-controlled tensile testing machines | 40 |
| Annex B | (normative) Types of test pieces to be used for thin products: sheets, strips, and flats between 0,1 mm and 3 mm thick | 46 |
| Annex C | (normative) Types of test pieces to be used for wire, bars, and sections with a diameter or thickness of less than 4 mm | 49 |
| Annex D | (normative) Types of test pieces to be used for sheets and flats of thickness equal to or greater than 3 mm and wire, bars, and sections of diameter or thickness equal to or greater than 4 mm | 50 |
| Annex E | (normative) Types of test pieces to be used for tubes | 54 |
| Annex F | (informative) Estimation of the crosshead separation rate in consideration of the stiffness (or compliance) of the testing equipment | 56 |
| Annex G | (normative) Determination of the modulus of elasticity of metallic materials using a uniaxial tensile test | 58 |
| Annex H | (informative) Measuring the percentage elongation after fracture if the specified value is less than 5 % | 66 |
| Annex I | (informative) Measurement of percentage elongation after fracture based on subdivision of the original gauge length | 67 |
| Annex J | (informative) Determination of the percentage plastic elongation without necking, A_{wn}, for long products such as bars, wire, and rods | 69 |
| Annex K | (informative) Estimation of the uncertainty of measurement | 70 |
| Annex L | (informative) Precision of tensile testing — Results from interlaboratory programmes | 74 |
| | Bibliography | 81 |