

DIN EN ISO 6892-1:2020-06 (E)

Metallic materials - Tensile testing - Part 1: Method of test at room temperature (ISO 6892-1:2019)

Contents	Page
European foreword	4
Foreword	5
Introduction.....	6
1 Scope	7
2 Normative references	7
3 Terms and definitions	7
4 Symbols	12
5 Principle	14
6 Test pieces	14
6.1 Shape and dimensions.....	14
6.1.1 General.....	14
6.1.2 Machined test pieces.....	15
6.1.3 Unmachined test pieces.....	15
6.2 Types.....	15
6.3 Preparation of test pieces.....	16
7 Determination of original cross-sectional area	16
8 Original gauge length and extensometer gauge length	16
8.1 Choice of the original gauge length.....	16
8.2 Marking the original gauge length.....	17
8.3 Choice of the extensometer gauge length.....	17
9 Accuracy of testing apparatus	17
10 Conditions of testing	17
10.1 Setting the force zero point.....	17
10.2 Method of gripping.....	17
10.3 Testing rates.....	18
10.3.1 General information regarding testing rates.....	18
10.3.2 Testing rate based on strain rate (method A).....	18
10.3.3 Testing rate based on stress rate (method B).....	20
10.3.4 Report of the chosen testing conditions.....	21
11 Determination of the upper yield strength	21
12 Determination of the lower yield strength	22
13 Determination of proof strength, plastic extension	22
14 Determination of proof strength, total extension	22
15 Method of verification of permanent set strength	23
16 Determination of the percentage yield point extension	23
17 Determination of the percentage plastic extension at maximum force	23
18 Determination of the percentage total extension at maximum force	23
19 Determination of the percentage total extension at fracture	24
20 Determination of percentage elongation after fracture	24
21 Determination of percentage reduction of area	25
22 Test report	25

23	Measurement uncertainty	26
23.1	General.....	26
23.2	Test conditions.....	26
23.3	Test results.....	26
Annex A	(informative) Recommendations concerning the use of computer-controlled tensile testing machines	40
Annex B	(normative) Types of test pieces to be used for thin products: sheets, strips, and flats between 0,1 mm and 3 mm thick	46
Annex C	(normative) Types of test pieces to be used for wire, bars, and sections with a diameter or thickness of less than 4 mm	49
Annex D	(normative) Types of test pieces to be used for sheets and flats of thickness equal to or greater than 3 mm and wire, bars, and sections of diameter or thickness equal to or greater than 4 mm	50
Annex E	(normative) Types of test pieces to be used for tubes	54
Annex F	(informative) Estimation of the crosshead separation rate in consideration of the stiffness (or compliance) of the testing equipment	56
Annex G	(normative) Determination of the modulus of elasticity of metallic materials using a uniaxial tensile test	58
Annex H	(informative) Measuring the percentage elongation after fracture if the specified value is less than 5 %	66
Annex I	(informative) Measurement of percentage elongation after fracture based on subdivision of the original gauge length	67
Annex J	(informative) Determination of the percentage plastic elongation without necking, A_{wn}, for long products such as bars, wire, and rods	69
Annex K	(informative) Estimation of the uncertainty of measurement	70
Annex L	(informative) Precision of tensile testing — Results from interlaboratory programmes	74
	Bibliography	81