

ISO 18086:2019-12 (E)

Corrosion of metals and alloys - Determination of AC corrosion - Protection criteria

| Contents | | Page |
|--------------------|--|-------------|
| Foreword | | v |
| Introduction | | vi |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 1 |
| 4 | Cathodic protection persons competence | 5 |
| 5 | Assessment of the AC influence | 5 |
| 5.1 | General | 5 |
| 5.2 | Assessment of the level of interference | 6 |
| 6 | Evaluation of the AC corrosion likelihood | 6 |
| 6.1 | Prerequisite | 6 |
| 6.1.1 | General | 6 |
| 6.1.2 | AC voltage on the structure | 7 |
| 6.2 | AC and DC current density | 7 |
| 6.2.1 | General | 7 |
| 6.2.2 | AC current density | 7 |
| 6.2.3 | High cathodic DC current density | 7 |
| 6.2.4 | Low cathodic DC current density | 8 |
| 6.2.5 | Current ratio "I _{a.c.} /I _{d.c.} " | 8 |
| 6.2.6 | Soil resistivity | 8 |
| 6.3 | Corrosion rate | 8 |
| 6.4 | Pipeline coatings | 8 |
| 6.5 | Evaluation of the metal loss | 9 |
| 7 | Acceptable interference levels | 9 |
| 8 | Measurement techniques | 9 |
| 8.1 | Measurements | 9 |
| 8.1.1 | General | 9 |
| 8.1.2 | Selection of test sites | 9 |
| 8.1.3 | Selection of measurement parameter | 10 |
| 8.1.4 | Sampling rate for the recording of interference levels | 10 |
| 8.1.5 | Accuracy of measuring equipment | 10 |
| 8.1.6 | Installation of coupons or probes to calculate current densities | 10 |
| 8.2 | DC potential measurements | 10 |
| 8.3 | AC voltage measurements | 11 |
| 8.4 | Measurements on coupons and probes | 11 |
| 8.4.1 | Installation of coupons or probes | 11 |
| 8.4.2 | Current measurements | 12 |
| 8.4.3 | Corrosion rate measurements | 12 |
| 8.5 | Pipeline metal loss techniques | 13 |
| 9 | Mitigation measures | 13 |
| 9.1 | General | 13 |
| 9.2 | Construction measures | 13 |

| | | |
|-----------------------|--|----|
| 9.2.1 | Modification of bedding material | 13 |
| 9.2.2 | Installation of isolating joints | 13 |
| 9.2.3 | Installation of mitigation wires | 14 |
| 9.2.4 | Optimization of pipeline and/or powerline route | 14 |
| 9.2.5 | Power line or pipeline construction | 14 |
| 9.3 | Operation measures | 14 |
| 9.3.1 | Earthing | 14 |
| 9.3.2 | Adjustment of cathodic protection level | 15 |
| 9.3.3 | Repair of coating defects | 15 |
| 10 | Commissioning | 16 |
| 10.1 | Commissioning | 16 |
| 10.2 | Preliminary checking | 16 |
| 10.2.1 | General | 16 |
| 10.2.2 | Coupon AC voltage and current startup | 17 |
| 10.2.3 | Verification of effectiveness | 17 |
| 10.2.4 | Installation and commissioning documents | 17 |
| 11 | Monitoring and maintenance | 18 |
| Annex A (informative) | Simplified description of the AC corrosion phenomenon | 19 |
| Annex B (informative) | Coupons and probes | 21 |
| Annex C (informative) | Coulometric oxidation | 26 |
| Annex D (informative) | Influence of soil characteristics on the AC corrosion process | 27 |
| Annex E (informative) | Other criteria that have been used in the presence of AC influence | 28 |
| Annex F (informative) | Parameters to take into account to choose a DC decoupling device | 32 |
| Annex G (informative) | Method to determine the reference electrode location to remote earth | 34 |
| Annex H (informative) | Simultaneous measurement on coupon current densities with high rate | 36 |
| Bibliography | | 38 |