

# ISO 20890-5:2020 (E)

## Guidelines for in-service inspections for primary coolant circuit components of light water reactors — Part 5: Eddy current testing of steam generator heating tubes

---

### Contents

	Foreword
1	Scope
2	Normative references
3	Terms and definitions
4	Inspection technique
4.1	Preliminary remark
4.2	General
4.3	Standard technique
4.3.1	Multiple frequency technique with internal bobbin probe in differential arrangement
4.3.1.1	Basic frequency
4.3.1.2	Comparison between the signals of several individual frequencies with internal bobbin probe
4.3.2	Linking the signals of multiple frequencies with internal bobbin probe in differential arrangement (mixed technique)
4.3.2.1	General
4.3.2.2	Two-frequency mix
4.3.2.3	Three-frequency mix
4.3.3	Multifrequency system with internal bobbin probe in absolute arrangement
4.4	Inspection techniques for more extensive analyses
5	Requirements
5.1	Test personnel
5.1.1	Task of NDT personnel
5.1.2	Personnel requirements
5.2	Steam generator heating tubes
5.3	Eddy current test equipment
5.3.1	General
5.3.2	Test robot
5.3.3	Eddy current test system
5.3.3.1	General
5.3.3.2	Requirements for the eddy current test device
5.3.3.3	Requirements for the probes
5.3.3.4	Requirements for the connecting cables
5.3.3.5	Requirements for reference specimens and calibration block
5.3.3.5.1	General
5.3.3.5.2	Reference specimen for determining the evaluation characteristic curves during calibration of the standard test systems
5.3.3.5.3	Calibration block for checking the eddy current test system
5.3.4	Assistant analysis system
5.4	Data storage medium
6	Testing
6.1	General
6.2	Preparations
6.3	Implementation
6.3.1	General
6.3.2	Data acquisition
6.3.3	Data analysis

- 6.3.3.1 General
- 6.3.3.2 Calibration
- 6.3.3.3 Data evaluation
- 6.3.3.4 Assessment of measuring data
- 6.4 Final measures

**7 Recording**

- 7.1 Test record and test report
- 7.2 Indication list
- 7.3 Findings record

**Annex A (informative) General test procedure**

**Page count: 19**