## ISO 16283-2:2020 (E)

## Acoustics — Field measurement of sound insulation in buildings and of building elements — Part 2: Impact sound insulation

## **Contents**

		Foreword			
		Introduction			
1		Scope			
2		Normative references			
3		Terms and definitions			
4		Instrumentation			
	4.1 4.2 4.3	General Calibration Verification			
5		Frequency range			
	5.1 5.2	Tapping machine as the impact source Rubber ball as the impact source			
6		General			
7		Default procedure for sound pressure level measurement			
7	7.1 7.2 7.2.1 7.2.2 7.2.3 7.3 7.3.1 7.3.2 7.3.3 7.4 7.4.1 7.4.2 7.4.3 7.5 7.5.1 7.5.2	General Generation of sound field General Impact source positions for the tapping machine as impact source Impact source positions for the rubber ball as impact source Fixed microphone positions for the tapping machine or rubber ball as impact source General Number of measurements Tapping machine operated at more than one position Rubber ball operated at more than one position Mechanized continuously moving microphone for the tapping machine as impact source General Number of measurements Tapping machine operated at more than one position Manually scanned microphone for the tapping machine as impact source General Number of measurements Tapping machine operated at more than one position			
	7.5.4 7.5.5 7.5.6 7.5.7 7.6 7.7.1 7.7.2 7.7.3 7.8	Helix Cylindrical-type Three semicircles Minimum distances for microphone positions Averaging times for the tapping machine as impact source Fixed microphone positions Mechanized continuously moving microphone Manually scanned microphone Calculation of energy-average sound pressure levels			

	7.8.2		Mechanized continuously moving microphone and manually scanned microphone for the tapping machine as impact source			
	7.8.3	3	Fixed microphone positions for the rubber ball as impact source			
8			requency procedure for sound pressure level measurement for the tapping machine as it source			
	8.1		General			
	8.2		Generation of sound field			
	8.2.	-	General			
	8.2.2	2	Impact source positions			
	8.3		Microphone positions			
	8.4 8.5		Averaging time Calculation of low-frequency energy-average impact sound pressure levels			
9		Background noise (default and low-frequency procedure)				
	9.1		General			
	9.2		Correction to the signal level for background noise			
10			beration time in the receiving room (default and low-frequency procedure)			
	10.1		General			
	10.2 10.3		Generation of sound field			
	10.3		Default procedure Low-frequency procedure			
	10.5		Interrupted noise method			
	10.6		Integrated impulse response method			
11		Conve	ersion to octave bands			
12		Expre	ssion of results			
13		Uncer	ertainty			
14		Test r	onort			
	. A					
Annex		(norm	ative) Impact sources			
	A.1.	1	Standard tapping machine Requirements			
	A.1.	-	Regular checks of performance			
	A.2 A.2.1 A.2.2		Rubber ball			
			Requirements			
			Example of construction of the rubber ball			
	A.2.	3	Regular checks of performance			
Annex	κВ	(norm	ative) Requirements for loudspeakers used for reverberation time measurements			
	B.1		General Control of the state of			
	B.2		Qualification procedure for directivity			
Annex	C	(inforr	mative) Forms for the expression of results			
Annex	( D	(inforr	mative) Additional guidance			
	D.1		General			
	D.2	_	Principles			
	D.2.		Floor coverings			
	D.2.		Calculation of room volumes			
	D.2. D.2.		Calculation of common partition area  Number of microphone and impact source positions			
	D.2.	7	Horizontal measurements			
D.3 D.4			Vertical measurements			
	D.4.	1	General			
	D.4.	2	Partly divided rooms			
D.4			Non-staggered rooms			
	D.4.		General			
	D.4.	3.2	Rooms with floor area of the source room equal to or less than the floor area of the receiving room			
			-			

D.4.	3.3 Rooms with floor area of the source room larger than the floor area of the receiving
	room
D.4.	Staggered rooms Corridors and staircases Measurements of impact sound insulation from a corridor Measurements of impact sound insulation from staircases in apartment houses and internal stairs in apartments and terrace houses
D.5	
D.5.	
D.5.	
D.6	Airborne sound contribution from the tapping machine
Annex E	(informative) Horizontal measurements — Examples of suitable impact source and microphone positions
E.1	General
E.2	Symbols
Annex F	(informative) Vertical measurements — Examples of suitable impact source and microphone positions $% \left( 1\right) =\left( 1\right) \left( 1$
F.1	General
F.2	Symbols

Page count: 44