

ISO 22232-1:2020 (E)

Non-destructive testing — Characterization and verification of ultrasonic test equipment — Part 1: Instruments

Contents

| | |
|---------|-------------------------------------------------------------------|
| | Foreword |
| 1 | Scope |
| 2 | Normative references |
| 3 | Terms and definitions |
| 4 | Symbols |
| 5 | General requirements of conformity |
| 6 | Manufacturer's technical specification for ultrasonic instruments |
| 7 | Performance requirements for ultrasonic instruments |
| 8 | Group 1 tests |
| 8.1 | Equipment required for group 1 tests |
| 8.2 | Battery operational time |
| 8.2.1 | Procedure |
| 8.2.2 | Acceptance criterion |
| 8.3 | Stability after warm-up time |
| 8.3.1 | Procedure |
| 8.3.2 | Acceptance criteria |
| 8.4 | Stability against temperature |
| 8.4.1 | Procedure |
| 8.4.2 | Acceptance criterion |
| 8.5 | Stability against voltage variation |
| 8.5.1 | Procedure |
| 8.5.2 | Acceptance criterion |
| 8.6 | Time base deviation |
| 8.6.1 | Procedure |
| 8.6.2 | Acceptance criterion |
| 8.7 | Transmitter pulse parameters |
| 8.7.1 | General |
| 8.7.2 | Pulse repetition frequency |
| 8.7.2.1 | Procedure |
| 8.7.2.2 | Acceptance criterion |
| 8.7.3 | Effective output impedance |
| 8.7.3.1 | Procedure |
| 8.7.3.2 | Acceptance criterion |
| 8.8 | Receiver |
| 8.8.1 | General |
| 8.8.2 | Cross talk from transmitter to receiver during transmission |
| 8.8.2.1 | Procedure |
| 8.8.2.2 | Acceptance criterion |
| 8.8.3 | Dead time after transmitter pulse |
| 8.8.3.1 | Procedure |
| 8.8.3.2 | Acceptance criterion |
| 8.8.4 | Dynamic range and maximum input voltage |
| 8.8.4.1 | Procedure |
| 8.8.4.2 | Acceptance criteria |
| 8.8.5 | Receiver input impedance |

- 8.8.5.1 Procedure
- 8.8.5.2 Acceptance criterion
- 8.8.6 Time-corrected gain (TCG)
- 8.8.6.1 Procedure
- 8.8.6.2 Acceptance criterion
- 8.9 Gates
- 8.9.1 General
- 8.9.2 Gates with value output
 - 8.9.2.1 Linearity of the amplitude in the gate
 - 8.9.2.1.1 Procedure
 - 8.9.2.1.2 Acceptance criterion
 - 8.9.2.2 Linearity of time of flight in the gate
 - 8.9.2.2.1 Procedure
 - 8.9.2.2.2 Acceptance criterion
- 8.9.3 Gates with analogue output
 - 8.9.3.1 Impedance of analogue output
 - 8.9.3.1.1 Procedure
 - 8.9.3.1.2 Acceptance criterion
 - 8.9.3.2 Linearity of analogue output
 - 8.9.3.2.1 Procedure
 - 8.9.3.2.2 Acceptance criterion
 - 8.9.3.3 Influence of the signal position within the gate
 - 8.9.3.3.1 Procedure
 - 8.9.3.3.2 Acceptance criterion
- 8.9.3.4 Rise time, fall time, delay time and hold time of analogue output
 - 8.9.3.4.1 Procedure
 - 8.9.3.4.2 Acceptance criterion
- 8.9.4 Gates with alarm output
 - 8.9.4.1 General
 - 8.9.4.2 Response threshold and switching hysteresis
 - 8.9.4.2.1 Procedure
 - 8.9.4.2.2 Acceptance criteria
 - 8.9.4.3 Delay time and hold time of the gate alarm
 - 8.9.4.3.1 Procedure
 - 8.9.4.3.2 Acceptance criteria
- 8.10 Highest digitized frequency
 - 8.10.1 Procedure
 - 8.10.1.1 General
 - 8.10.1.2 Method A
 - 8.10.1.3 Method B
 - 8.10.2 Acceptance criterion
- 8.11 Response time of digital ultrasonic instruments
 - 8.11.1 General
 - 8.11.2 Procedure
 - 8.11.3 Acceptance criterion

9 Group 2 tests

- 9.1 Equipment required for group 2 tests
- 9.2 Physical state and external aspects
 - 9.2.1 Procedure
 - 9.2.2 Acceptance criterion
- 9.3 Transmitter voltage, pulse rise time and duration
 - 9.3.1 Procedure
 - 9.3.2 Acceptance criteria
- 9.4 Receiver
 - 9.4.1 General
 - 9.4.2 Frequency response
 - 9.4.2.1 Procedure
 - 9.4.2.2 Acceptance criteria
 - 9.4.3 Noise level
 - 9.4.3.1 Procedure
 - 9.4.3.2 Method A
 - 9.4.3.3 Method B
 - 9.4.3.4 Acceptance criterion

- 9.4.4** **Gain linearity**
- 9.4.4.1** **Procedure**
- 9.4.4.2** **Acceptance criteria**
- 9.4.5** **Vertical display linearity**
- 9.4.5.1** **Procedure**
- 9.4.5.2** **Acceptance criteria**

Annex A (normative) Special conditions for ultrasonic instruments with logarithmic amplifiers

- A.1** **General**
- A.2** **Basic requirements**
- A.2.1** **Measuring accuracy**
- A.2.2** **Vertical linearity**
- A.2.3** **Tests**

Page count: 40