

DIN EN 12543-2:2021-06 (E)

Non-destructive testing - Characteristics of focal spots in industrial X-ray systems for use in non-destructive testing - Part 2: Pinhole camera radiographic method

| Contents | | Page |
|---|--|-------------|
| European foreword | | 3 |
| Introduction | | 4 |
| 1 | Scope | 5 |
| 2 | Normative references | 5 |
| 3 | Terms and definitions | 5 |
| 4 | Test equipment | 6 |
| 4.1 | Essential characteristics of the pinhole | 6 |
| 4.2 | Alignment and position of the pinhole camera | 7 |
| 4.3 | Position of the radiographic image detector | 8 |
| 4.4 | Requirements on the radiographic image detector | 9 |
| 4.5 | Image processing equipment for digital images | 10 |
| 4.6 | Loading factors | 10 |
| 5 | Measurement and determination of the focal spot size | 10 |
| 5.1 | Measurement procedure | 10 |
| 5.2 | Measurement with digital technique (preferred method) | 12 |
| 5.3 | Evaluation with digital technique using Integrated Line Profiles (ILP) | 12 |
| 5.4 | Measurement of effective focal spot size visually using film radiographs | 15 |
| 6 | Classification and result of focal spot size measurement | 15 |
| Annex A(normative) Values for the classification of X-ray tube focal spot sizes | | 17 |
| Bibliography | | 19 |