

DIN EN ISO 3452-2:2022-02 (E)

Non-destructive testing - Penetrant testing - Part 2: Testing of penetrant materials (ISO 3452-2:2021)

| Contents | | Page |
|------------------------------------------------------|-------|-------------|
| European foreword | | 4 |
| Foreword | | 5 |
| 1 Scope | | 6 |
| 2 Normative references | | 6 |
| 3 Terms and definitions | | 6 |
| 4 Classification | | 7 |
| 4.1 Testing products | | 7 |
| 4.2 Sensitivity levels | | 7 |
| 4.2.1 General | | 7 |
| 4.2.2 Penetrant baseline sensitivity | | 7 |
| 4.2.3 Product family sensitivity | | 7 |
| 4.2.4 Fluorescent systems | | 7 |
| 4.2.5 Colour contrast systems | | 8 |
| 4.2.6 Dual-purpose product family | | 8 |
| 5 Testing of penetrant materials | | 8 |
| 5.1 Personnel | | 8 |
| 5.2 Testing facilities | | 8 |
| 5.2.1 Type testing | | 8 |
| 5.2.2 Batch testing | | 8 |
| 5.2.3 Process and control testing | | 8 |
| 5.3 Reporting | | 8 |
| 5.3.1 Type testing | | 8 |
| 5.3.2 Batch testing | | 9 |
| 5.4 Tests | | 9 |
| 5.4.1 Sensitivity test | | 9 |
| 5.4.2 Penetrants | | 9 |
| 5.4.3 Excess penetrant removers (excluding method A) | | 9 |
| 5.4.4 Developers | | 10 |
| 5.4.5 Batch tests for spray cans | | 10 |
| 6 Test methods and requirements | | 10 |
| 6.1 Appearance | | 10 |
| 6.2 Penetrant system sensitivity | | 11 |
| 6.2.1 Fluorescent penetrants (type I) | | 11 |
| 6.2.2 Colour contrast penetrants (type II) | | 14 |
| 6.3 Density | | 15 |
| 6.3.1 Test method | | 15 |
| 6.3.2 Requirements | | 15 |
| 6.4 Viscosity | | 15 |
| 6.4.1 Test method | | 15 |
| 6.4.2 Requirements | | 15 |
| 6.5 Flashpoint | | 15 |
| 6.5.1 Test method | | 15 |
| 6.5.2 Requirements | | 16 |
| 6.6 Washability (method A penetrants) | | 16 |

| | | |
|----------|-----------------------------------------------------------------------------------------------------------|-----------|
| 6.7 | Fluorescent brightness | 16 |
| 6.7.1 | Test method | 16 |
| 6.7.2 | Requirements | 16 |
| 6.8 | UV stability | 16 |
| 6.8.1 | Test method | 16 |
| 6.8.2 | Requirements | 16 |
| 6.9 | Thermal stability of fluorescent brightness | 17 |
| 6.9.1 | Test method | 17 |
| 6.9.2 | Requirements | 17 |
| 6.10 | Water tolerance | 17 |
| 6.10.1 | Test method | 17 |
| 6.10.2 | Requirements | 18 |
| 6.11 | Corrosive properties | 18 |
| 6.11.1 | General | 18 |
| 6.11.2 | Type testing | 18 |
| 6.11.3 | Batch testing | 21 |
| 6.12 | Content of sulfur and halogens (for products designated low in sulfur and halogens) | 21 |
| 6.12.1 | Test method | 21 |
| 6.12.2 | Requirements | 21 |
| 6.13 | Residue on evaporation/solid content | 22 |
| 6.13.1 | Solvent removers | 22 |
| 6.13.2 | Form d and e developers | 22 |
| 6.14 | Penetrant tolerance | 22 |
| 6.14.1 | Lipophilic emulsifier (method B) | 22 |
| 6.14.2 | Hydrophilic emulsifier (method D) | 22 |
| 6.15 | Developer performance | 22 |
| 6.16 | Re-dispersability | 22 |
| 6.16.1 | Water-suspendable developers | 22 |
| 6.16.2 | Solvent based developers (non-aqueous) | 22 |
| 6.17 | Density of carrier liquid | 23 |
| 6.17.1 | Test method | 23 |
| 6.17.2 | Requirements | 23 |
| 6.18 | Product performance (pressurized containers) | 23 |
| 6.19 | Particle size distribution | 23 |
| 6.20 | Water content | 23 |
| 6.20.1 | Test method | 23 |
| 6.20.2 | Requirements | 23 |
| 7 | Packaging and labelling | 23 |
| | Annex A (normative) Comparison of fluorescent brightness | 24 |
| | Annex B (normative) Equipment for determination of the visibility of fluorescent indications | 26 |
| | Annex C (informative) List of reference materials | 27 |
| | Bibliography | 29 |