

ISO 1143:2021 (E)

Metallic materials — Rotating bar bending fatigue testing

Contents

| | |
|---------|---|
| | Foreword |
| 1 | Scope |
| 2 | Normative references |
| 3 | Terms and definitions |
| 4 | Symbols |
| 5 | Principle of test |
| 6 | Shape and size of specimen |
| 6.1 | Forms of the test section |
| 6.2 | Dimensions of specimens |
| 7 | Preparation of specimens |
| 7.1 | General |
| 7.2 | Selection of the specimen and marking |
| 7.3 | Machining procedure |
| 7.3.1 | Heat treatment of test material |
| 7.3.2 | Machining criteria |
| 7.3.3 | Surface condition of specimens |
| 7.3.4 | Dimensional checks |
| 7.4 | Storage and handling |
| 8 | Accuracy of the testing apparatus |
| 9 | Heating device and temperature measurement |
| 10 | Test procedure |
| 10.1 | Mounting the specimen |
| 10.2 | Application of force |
| 10.3 | Frequency selection |
| 10.4 | End of test |
| 10.5 | Procedure for testing at elevated temperature |
| 11 | Test report |
| 12 | Presentation of fatigue test results |
| 12.1 | Tabular presentation |
| 12.2 | Graphical presentation |
| 13 | Measurement uncertainty |
| 13.1 | General |
| 13.2 | Test conditions |
| 13.3 | Test results |
| Annex A | (normative) Verification of the bending moment of rotating bar bending fatigue machines |
| A.1 | Verification philosophies for rotating bar bending fatigue machines |
| A.2 | Verification equipment |
| A.2.1 | General |
| A.2.2 | Masses |
| A.2.3 | Force transducers |

- A.2.4 Dimensional measurement
- A.3 Inspection of the test machine prior to verification
- A.4 Verification procedure — Verification by dimensional measurement
 - A.4.1 General
 - A.4.2 Temperature stabilization
 - A.4.3 Measurement of mean force arm length
 - A.4.4 Measurement of loading arm lever ratio
 - A.4.5 Calculation of required characteristics — Relative force accuracy error, q
 - A.4.5.1 Machines incorporating force transducer(s)
 - A.4.5.2 Machines using test masses
 - A.4.5.3 Machines using steelyard and balance loading
 - A.4.6 Calculation of required characteristics — Relative force repeatability error, b
 - A.4.6.1 Machines incorporating force transducer(s); i.e. force transducer(s)
 - A.4.6.2 Machines using test masses
 - A.4.6.3 Machines using steelyard and balance loading
 - A.4.7 Calculation of required characteristics — Relative force arm accuracy error, q'
 - A.4.8 Calculation of required characteristics — Relative moment accuracy error, q''
 - A.4.9 Required performance characteristics
- A.5 Verification procedure — Verification using strain-gauged specimen
 - A.5.1 General
 - A.5.2 Temperature stabilization
 - A.5.3 Pre-verification conditioning
 - A.5.4 Selection of test forces
 - A.5.5 Cantilever machines
 - A.5.6 Four-point bending machines
 - A.5.7 Machines verified using a strain-gauged specimen
 - A.5.8 Calculation of required characteristics — Relative force accuracy error, q
 - A.5.8.1 Machines incorporating force transducer(s)
 - A.5.8.2 Machines using test masses
 - A.5.8.3 Machines using steelyard and balance loading
 - A.5.9 Calculation of required characteristics — Relative force repeatability error, b
 - A.5.9.1 Machines incorporating force transducer(s); i.e. force transducer(s)
 - A.5.9.2 Machines using test masses
 - A.5.9.3 Machines using steelyard and balance loading
 - A.5.10 Required performance characteristics
- A.6 Verification period

Annex B (informative) Example of a test report

Page count: 26