

# DIN EN ISO 17636-1:2022-10 (E)

## Non-destructive testing of welds - Radiographic testing - Part 1: X- and gamma-ray techniques with film (ISO 17636-1:2022)

---

<b>Contents</b>		<b>Page</b>
<b>European foreword</b> .....		<b>4</b>
<b>Foreword</b> .....		<b>5</b>
<b>1</b>	<b>Scope</b> .....	<b>7</b>
<b>2</b>	<b>Normative references</b> .....	<b>7</b>
<b>3</b>	<b>Terms and definitions</b> .....	<b>8</b>
<b>4</b>	<b>Symbols and abbreviated terms</b> .....	<b>9</b>
<b>5</b>	<b>Classification of radiographic techniques</b> .....	<b>10</b>
<b>6</b>	<b>General preparations and requirements</b> .....	<b>10</b>
6.1	Protection against ionizing radiation .....	10
6.2	Surface preparation and stage of manufacture .....	10
6.3	Location of the weld in the radiograph .....	11
6.4	Identification of radiographs .....	11
6.5	Marking .....	11
6.6	Overlap of films .....	11
6.7	Types and positions of image quality indicators (IQIs) .....	11
6.8	Evaluation of image quality .....	12
6.9	Minimum image quality values .....	12
6.10	Personnel qualification .....	13
<b>7</b>	<b>Recommended techniques</b> .....	<b>13</b>
7.1	Test arrangements .....	13
7.1.1	General .....	13
7.1.2	Single-wall penetration of plane objects (see <a href="#">Figure 1</a> ) .....	14
7.1.3	Single-wall penetration of curved objects with the source outside the object (see <a href="#">Figures 2 to 4</a> ) .....	14
7.1.4	Single-wall penetration of curved objects with the source inside the object for panoramic exposure (see <a href="#">Figures 5 to 7</a> ) .....	15
7.1.5	Single-wall penetration of curved objects with the source located off-centre and inside the object (see <a href="#">Figures 8 to 10</a> ) .....	16
7.1.6	Double-wall penetration and double-image evaluation (DWDI) of pipes with the elliptic technique and the source and the film outside the object (see <a href="#">Figure 11</a> ) .....	17
7.1.7	Double-wall penetration and double-image evaluation (DWDI) with the perpendicular technique and source and film outside the object (see <a href="#">Figure 12</a> ) .....	17
7.1.8	Double-wall penetration and single-image evaluation (DWSI) of curved objects for evaluation of the wall next to the film (see <a href="#">Figures 13 to 16</a> ) .....	17
7.1.9	Penetration of objects with different material thicknesses (see <a href="#">Figure 17 to 19</a> ) .....	19
7.2	Choice of tube voltage and radiation source .....	19
7.2.1	X-ray devices up to 1 000 kV .....	19
7.2.2	Other radiation sources .....	20
7.3	Film systems and metal screens .....	21
7.4	Alignment of beam .....	23
7.5	Reduction of scattered radiation .....	23
7.5.1	Metal filters and collimators .....	23
7.5.2	Interception of backscattered radiation .....	23

7.6	Source-to-object distance.....	24
7.7	Maximum area for a single exposure.....	26
7.8	Optical density of radiograph.....	26
7.9	Processing.....	27
7.10	Film viewing conditions.....	27
<b>8</b>	<b>Test report.....</b>	<b>27</b>
<b>Annex A</b>	<b>(normative) Number of exposures for acceptable testing of a circumferential butt weld.....</b>	<b>29</b>
<b>Annex B</b>	<b>(normative) Minimum image quality values.....</b>	<b>34</b>
<b>Annex C</b>	<b>(informative) Calculation of maximum X-ray tube voltages from <a href="#">Figure 20</a>.....</b>	<b>41</b>
<b>Bibliography</b>	<b>.....</b>	<b>42</b>