

DIN EN ISO 17636-2:2023-05 (E)

Non-destructive testing of welds - Radiographic testing - Part 2: X- and gamma-ray techniques with digital detectors (ISO 17636-2:2022, Corrected version 2023-02)

Contents		Page
European foreword		4
Foreword.....		5
1	Scope	7
2	Normative references	7
3	Terms and definitions	8
4	Symbols and abbreviated terms	12
5	Classification of radiographic techniques and compensation principles	14
5.1	Classification.....	14
5.2	Compensation principles, CP I, CP II or CP III.....	14
5.2.1	General.....	14
5.2.2	Compensation principle I (CP I).....	14
5.2.3	Compensation principle II (CP II).....	14
5.2.4	Compensation principle III (CP III).....	14
5.2.5	Theoretical background.....	15
6	General preparations and requirements	15
6.1	Protection against ionizing radiation.....	15
6.2	Surface preparation and stage of manufacture.....	15
6.3	Location of the weld in the radiograph.....	15
6.4	Identification of radiographs.....	15
6.5	Marking.....	15
6.6	Overlap of digital images.....	16
6.7	Types and positions of image quality indicators (IQIs).....	16
6.7.1	General.....	16
6.7.2	Duplex wire IQIs.....	16
6.7.3	Single wire or step-hole IQIs.....	16
6.8	Evaluation of image quality.....	17
6.9	Minimum image quality values.....	18
6.10	Personnel qualification.....	18
7	Recommended techniques	19
7.1	Test arrangements.....	19
7.1.1	General.....	19
7.1.2	Single-wall penetration of plane objects (see Figure 1).....	20
7.1.3	Single-wall penetration of curved objects with the source outside the object (see Figures 2 to 4).....	20
7.1.4	Single-wall penetration of curved objects with the source inside the object for panoramic exposure (see Figures 5 to 7).....	21
7.1.5	Single-wall penetration of curved objects with the source located off-centre and inside the object (see Figures 8 to 10).....	22
7.1.6	Double-wall penetration and double-image evaluation (DWDI) of pipes with the elliptic technique and the source and the detector outside the object (see Figure 11).....	23
7.1.7	Double-wall penetration and double-image evaluation (DWDI) with the perpendicular technique and source and detector outside the object (see Figure 12).....	23
7.1.8	Double-wall penetration and single-image evaluation (DWSI) of curved objects for evaluation of the wall next to the detector (see Figures 13 to 16).....	24

7.1.9	Penetration of objects with different material thicknesses (see Figure 17 to 19)	25
7.2	Choice of tube voltage and radiation source	26
7.2.1	X-ray devices up to 1 000 kV	26
7.2.2	Other radiation sources	27
7.3	Detector systems and metal screens	28
7.3.1	Minimum normalized signal-to-noise ratio (SNR_N)	28
7.3.2	Compensation principle II	31
7.3.3	Metal screens for IPs and shielding	31
7.4	Alignment of beam	31
7.5	Reduction of scattered radiation	32
7.5.1	Metal filters and collimators	32
7.5.2	Interception of backscattered radiation	32
7.6	Source-to-object distance	32
7.7	Geometric magnification technique	39
7.8	Maximum area for a single exposure	40
7.9	Processing	40
7.9.1	Scan and read-out of images	40
7.9.2	Correction of acquired DDA images	41
7.9.3	Bad pixel interpolation	41
7.9.4	Image processing	41
7.10	Monitor viewing conditions and storage of digital radiographs	42
8	Test report	42
Annex A (normative)	Number of exposures for acceptable testing of a circumferential butt weld	44
Annex B (normative)	Minimum image quality values	49
Annex C (normative)	Determination of basic spatial resolution	57
Annex D (informative)	Determination of minimum grey values for CR practice	59
Annex E (informative)	Grey values — General remarks	64
Annex F (informative)	Considering the detector unsharpness for f_{min}	66
Annex G (informative)	Calculation of recommended X-ray tube voltages from Figure 20	69
	Bibliography	70