ISO 23838:2022-06 (E)

Metallic materials - High strain rate torsion test at room temperature

Contents

Page

Foreword iv

Introduction v

1 Scope 1

2 Normative references 1

3 Termsanddefinitions 1

4 Symbols and designations 2

5 Principle 4

6 Apparatus 5
6.1 Apparatus components 5
6.2 Loading device 6
6.3 Bar components 6
6.4 Data acquisition and recording system 7

7 Test piece 7
7.1 Dimensions of test piece 7
7.2 Measurement of test piece dimensions 9

8 Procedure 9
8.1 Calibration of the apparatus 9
8.2 Recording the temperature of the test environment 10
8.3 Checking the bar alignment 10
8.4 Mounting test piece 10
8.5 Loading 11
8.6 Measuring and recording 11

9 Data processing 11
9.1 Strain on bars 11
9.2 Waveform processing 11
9.2.1 Determination of waveform baseline 11
9.2.2 Determination of starting points of waves 11
9.2.3 Synchronization of waves 12
9.2.4 Determination of loading duration of stress wave 12
9.3 Engineering plastic shear strain rate 12
9.4 Engineering plastic shear strain 12
9.5 Engineering plastic shear stress 12
9.6 Engineering plastic shear stress-shear strain curve 12
9.7 Average engineering plastic shear strain rate 12
9.8 Test example 13

10 Evaluation of test result 13

11 Test report 13

Annex A (informative) Torsional split Hopkinson bar 14

Annex B (informative) Data acquisition and recording system 28

Annex C (informative) Method for determining the starting points of waves 31

Annex D (informative) Example of torsional split Hopkinson bar method 32

Bibliography 36