

ISO 17636-2:2022-09 (E)

Non-destructive testing of welds - Radiographic testing - Part 2: X- and gamma-ray techniques with digital detectors

Contents

| | Page |
|--|-----------|
| Foreword | v |
| 1 Scope | 1 |
| 2 Normative references | 1 |
| 3 Terms and definitions | 2 |
| 4 Symbols and abbreviated terms | 6 |
| 5 Classification of radiographic techniques and compensation principles | 8 |
| 5.1 Classification | 8 |
| 5.2 Compensation principles, CP I, CP II or CP III | 8 |
| 5.2.1 General | 8 |
| 5.2.2 Compensation principle I (CP I) | 8 |
| 5.2.3 Compensation principle II (CP II) | 8 |
| 5.2.4 Compensation principle III (CP III) | 8 |
| 5.2.5 Theoretical background | 9 |
| 6 General preparations and requirements | 9 |
| 6.1 Protection against ionizing radiation | 9 |
| 6.2 Surface preparation and stage of manufacture | 9 |
| 6.3 Location of the weld in the radiograph | 9 |
| 6.4 Identification of radiographs | 9 |
| 6.5 Marking | 9 |
| 6.6 Overlap of digital images | 10 |
| 6.7 Types and positions of image quality indicators (IQIs) | 10 |
| 6.7.1 General | 10 |
| 6.7.2 Duplex wire IQIs | 10 |
| 6.7.3 Single wire or step-hole IQIs | 10 |
| 6.8 Evaluation of image quality | 11 |
| 6.9 Minimum image quality values | 12 |
| 6.10 Personnel qualification | 12 |
| 7 Recommended techniques | 13 |
| 7.1 Test arrangements | 13 |
| 7.1.1 General | 13 |
| 7.1.2 Single-wall penetration of plane objects (see Figure 1) | 14 |
| 7.1.3 Single-wall penetration of curved objects with the source outside the object (see Figures 2 to 4) | 14 |
| 7.1.4 Single-wall penetration of curved objects with the source inside the object for panoramic exposure (see Figures 5 to 7) | 15 |
| 7.1.5 Single-wall penetration of curved objects with the source located off-centre and inside the object (see Figures 8 to 10) | 16 |
| 7.1.6 Double-wall penetration and double-image evaluation (DWI) of pipes with the elliptic technique and the source and the detector outside the object (see Figure 11) | 17 |
| 7.1.7 Double-wall penetration and double-image evaluation (DWI) with the perpendicular technique and source and detector outside the object (see Figure 12) | 17 |
| 7.1.8 Double-wall penetration and single-image evaluation (DWI) of curved objects for evaluation of the wall next to the detector (see Figures 13 to 16) | 18 |
| 7.1.9 Penetration of objects with different material thicknesses (see Figure 17 to 19) | 19 |

| | | |
|--|---|-----------|
| 7.2 | Choice of tube voltage and radiation source | 20 |
| 7.2.1 | X-ray devices up to 1 000 kV | 20 |
| 7.2.2 | Other radiation sources | 21 |
| 7.3 | Detector systems and metal screens | 22 |
| 7.3.1 | Minimum normalized signal-to-noise ratio (SNRN) | 22 |
| 7.3.2 | Compensation principle II | 25 |
| 7.3.3 | Metal screens for IPs and shielding | 25 |
| 7.4 | Alignment of beam | 25 |
| 7.5 | Reduction of scattered radiation | 26 |
| 7.5.1 | Metal filters and collimators | 26 |
| 7.5.2 | Interception of backscattered radiation | 26 |
| 7.6 | Source-to-object distance | 26 |
| 7.7 | Geometric magnification technique | 33 |
| 7.8 | Maximum area for a single exposure | 34 |
| 7.9 | Processing | 34 |
| 7.9.1 | Scan and read-out of images | 34 |
| 7.9.2 | Correction of acquired DDA images | 35 |
| 7.9.3 | Bad pixel interpolation | 35 |
| 7.9.4 | Image processing | 35 |
| 7.10 | Monitor viewing conditions and storage of digital radiographs | 36 |
| 8 | Test report | 36 |
| Annex A (normative) Number of exposures for acceptable testing of a circumferential butt weld | | 38 |
| Annex B (normative) Minimum image quality values | | 43 |
| Annex C (normative) Determination of basic spatial resolution | | 51 |
| Annex D (informative) Determination of minimum grey values for CR practice | | 53 |
| Annex E (informative) Grey values -- General remarks | | 58 |
| Annex F (informative) Considering the detector unsharpness for fmin | | 60 |
| Annex G (informative) Calculation of recommended X-ray tube voltages from Figure 20 | | 63 |
| Bibliography | | 64 |