ISO 24647:2023-02 (E)

Non-destructive testing - Robotic ultrasonic test systems - General requirements

Contents

Page

Foreword v

1 Scope 1

2 Normative references 1

3 Termsanddefinitions 1

4 Requirements for test personnel 2

5 Test system 2
5.1 General 2
5.2 Design principles 3
5.3 Test equipment 3
5.3.1 Instrument 3
5.3.2 Probes 3
5.3.3 Robots 3
5.3.4 Couplant 4
5.4 Typical test systems 4
5.4.1 Single-robot test system 4
5.4.2 Twin-robot test system 6

6 Characteristics and requirements for robotic ultrasonic test systems 9
6.1 General 9
6.2 Test technique 9
6.2.1 General 9
6.2.2 Pulse-echo technique 9
6.2.3 Trough-transmission technique 9
6.3 Planning of scan pattern and programming of robot motion control 9
6.3.1 General 9
6.3.2 Path planning method 9
6.3.3 Restrictions 12
6.4 Synchronisation of the acquisition of ultrasonic and position data 12
6.4.1 Synchronisation of ultrasonic signal and robot position 12
6.4.2 Synchronisation -- Minimum requirements 12
6.4.3 Synchronisation -- Optional requirements 13
6.5 Conditions for the application 13

7 Verificationofthetestsystem 13
7.1 General 13
7.2 Ultrasonic instrument and probes 14
7.2.1 General 14
7.2.2 Single-probe systems 14
7.2.3 Multi-probe systems 14
7.2.4 Normalization of pulse-echo systems 14
7.2.5 Normalization of through-transmission systems 14
7.3 Robots 14
7.4 Synchronization 15
7.5 Complete system -- Robots, instrument and probes combined 15
7.5.1 General 15
7.5.2 Signal-to-noise ratio 15
7.5.3 Image distortion coefficient 16

7.5.4 Detection sensitivity 16

8 Typical process of an automated test for a robotic ultrasonic test system 17
8.1 Preparation 17
8.2 Probes 17
8.3 Trajectory planning 17
8.4 Setup of the scanning reference coordinate system 17
8.5 Test procedure 17

9 Documentationoftheverificationresults 18

Annex A (informative) Trajectory planning 19

Annex B (informative)Exampleofaverificationreport 30

Bibliography 34