

ISO 18782:2023-05 (E)

Textiles - Determination of dynamic hygroscopic heat generation

| Contents | | Page |
|--|--|-------------|
| Foreword | | iv |
| Introduction | | v |
| 1 Scope | | 1 |
| 2 Normative references | | 1 |
| 3 Terms and definitions | | 1 |
| 4 Principle | | 2 |
| 5 Testing condition | | 2 |
| 5.1 Low humidity air | | 2 |
| 5.2 High humidity air | | 2 |
| 6 Reagents and materials | | 2 |
| 7 Apparatus | | 2 |
| 8 Conditioning atmosphere for sampling | | 6 |
| 9 Preparation of specimens | | 6 |
| 10 Test procedure | | 6 |
| 10.1 Mounting of test specimens | | 6 |
| 10.2 Pretreatment process immediately before measurement | | 6 |
| 10.3 Measurement process | | 6 |
| 11 Calculation | | 7 |
| 12 Test report | | 8 |
| Annex A (normative) Determination of the air flow rate for high humidity air | | 9 |
| Annex B (informative) Interlaboratory test results | | 11 |
| Annex C (informative) Example of a practical testing apparatus | | 15 |
| Annex D (informative) Example of an interpretation of the test result | | 16 |
| Bibliography | | 17 |