DIN EN 16906:2023-12 (E)

Liquid petroleum products - Determination of the ignition quality of diesel fuels - Fixed compression ratio engine method

Contents

Page

European foreword 4

Introduction 5

1 Scope 6

2 Normative references 6

3 Terms and definitions 6

4 Principle 7

5 Reagents and materials 7
5.1 Reference materials 7
5.2 Check fuels 8

6 Apparatus 8
6.1 General 8
6.2 Mechanical equipment 9
6.3 Electrical equipment 10
6.4 Reference fuel dispensing equipment 11

7 Sampling 11

8 Standard operating and test conditions 12

9 Calibration, verification and quality control 12

10 Procedure 12
10.1 Engine check and warm-up 12
10.2 Bracketing procedure 13
10.2.1 Unknown sample 13
10.2.2 First primary reference fuel 13
10.2.3 Second primary reference fuel 13
10.2.4 Repeat readings 14
10.3 Procedure using a calibration graph 14
10.4 Shut-down of the engine 15

11 Calculation 15
11.1 Calculation for the bracketing procedure 15
11.2 Calculation for the calibration graph 15

12 Expression of results 16

13 Precision 16
13.1 General 16
13.2 Repeatability 16
13.3 Reproducibility 16

Annex A (informative) Evaluation example of the cetane number using a calibration graph 17

Annex B (informative) Auxiliary digital equipment 18

B.1 General 18
B.2 Apparatus 18
B.2.1 Oil-pressure sensor, installed at the oil pressure line 18
B.2.2 Oil temperature sensor, combined with the additionally supplied oil dip-stick to be placed into the designated borehole 18
B.2.3 Exhaust gas temperature sensor, placed to the exhaust-pipe 18
B.2.4 Cooling-water temperature sensor, installed at the water elbow joint 18
B.2.5 Injection Pick-up, placed on the injection nozzle 18
B.2.6 Dead-Top Centre (DTC) Pick-up, installed at the fastener opposite to the flywheel 18
B.2.7 Combustion Pick-up, inductive pressure difference sensor or absolute pressure sensor.18 B.2.8 Vacuum sensor, installed at the entrance of the surge tank 18
B.2.9 Ambient sensor, for absolute air pressure, temperature and humidity 18
B.2.10 Intake air temperature sensor (optional), for monitoring the steady-state conditions for operating the engine 18
B.2.11 Diesel flow meter (optional), for measuring the diesel flow rate 18
B.3 Set-up 18
B.4 Calibration 19

Bibliography 20