

# DIN EN 1097-1:2024-02 (E)

## Tests for mechanical and physical properties of aggregates - Part 1: Determination of the resistance to wear (micro-Deval)

---

<b>Contents</b>		<b>Page</b>
European foreword .....		3
<b>1</b>	<b>Scope .....</b>	<b>5</b>
<b>2</b>	<b>Normative references .....</b>	<b>5</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>6</b>
<b>4</b>	<b>Principle .....</b>	<b>6</b>
<b>5</b>	<b>Apparatus .....</b>	<b>7</b>
<b>6</b>	<b>Preparation of test portion .....</b>	<b>8</b>
<b>7</b>	<b>Test procedure .....</b>	<b>9</b>
<b>8</b>	<b>Calculation and expression of results .....</b>	<b>9</b>
<b>9</b>	<b>Test report .....</b>	<b>10</b>
<b>9.1</b>	<b>Required data .....</b>	<b>10</b>
<b>9.2</b>	<b>Optional data .....</b>	<b>10</b>
<b>Annex A (normative) Determination of the resistance to wear (micro-Deval) of railway ballast .....</b>		<b>11</b>
<b>Annex B (informative) Determination of micro-Deval coefficient in the dry condition .....</b>		<b>13</b>
<b>Annex C (informative) Alternative narrow size fractions for the micro-Deval test .....</b>		<b>14</b>
<b>Annex D (informative) Determination of the abrasion coefficient of size fraction 0,25/5,6 mm .....</b>		<b>15</b>
<b>Annex E (informative) Determination of the friability coefficient of size fraction 0,2/2 mm (or 0,2/4 mm) .....</b>		<b>18</b>
<b>Annex F (informative) Precision for the reference test method .....</b>		<b>21</b>
<b>Bibliography .....</b>		<b>22</b>