DIN 51451:2024-03 (E)

Testing of petroleum products and related products - Analysis by infrared spectrometry - General working principles

Contents

Page

Foreword 4

1 Scope 5

2 Normative references 5

3 Terms and definitions 5

4 General 5
4.1 Theoretical principles 5
4.2 Units 7

5 Apparatus 7
5.1 IR spectrometer 7
5.1.1 General 7
5.1.2 Minimum requirements 7
5.2 Cuvettes 8
5.3 ATR (Attenuated Total Reflection) accessories 9
5.4 Other apparatus and tools 10

6 Reagents and equipment 10

7 Sample preparation 11

8 Preparation for measurement 11
8.1 Instrument checking and adjustment 11
8.1.1 Spectrometer 11
8.1.2 Recording a test spectrum 12
8.1.3 Determination of the instrument factor F 12
8.2 Path length measurement 13

9 Procedure 14
9.1 General 14
9.2 Spectral recording 14
9.3 Direct measurement 14
9.4 Differential spectrometry 14
9.5 Suspension procedure 14
9.6 KBr pressing procedure 15

10 Evaluation 15
10.1 Qualitative analysis 15
10.2 Quantitative analysis 15
10.2.1 General 15
10.2.2 Baseline method 15
10.2.3 Reference graph method 16
10.2.4 Standard addition method 17

11 Expression of results 17

12 Precision 17

Annex A (informative) Infrared spectrometers 18

A.1 Fourier transform infrared spectrometers (FT-IR spectrometers) 18
A.2 Attenuated Total Reflection (ATR) accessories 18

Bibliography 20

Figures Figure 1 -- Representation of a mean infrared transmission spectrum for ca. 40 µm thick polystyrene film in the range of 4 000 cm-1 to 400 cm-1 11

Figure 2 -- Example of a transmittance spectrum for polypropylene film with interference pattern for path length determination 13

Figure 3 -- Baseline method (linear absorbance ordinate) with two signals as examples 16

Figure A.1 -- Essential parts of an FT-IR spectrometer 18

Figure A.2 -- Essential parts of an ATR accessory for IR spectrometry 19

Tables Table 1 -- Common window materials 9

Table 2 -- Window materials commonly used in ATR technology 9

Table 3 -- Absorption for determining the instrument factor F 12

Table 4 -- Measurement ranges for path length measurement 13